

TITLE

METHODS AND APPARATUS FOR FACILITATING LOCALIZED NUCLEAR FUSION REACTIONS IN DEUTERATED METALS ENHANCED BY ELECTRON SCREENING

STATEMENT OF FEDERAL RIGHTS

[0001] This invention was made with government support under Contract Nos. NNC14CA16C and 80GRC017C0021 awarded by the National Aeronautics and Space Administration (NASA). The Government has certain rights in the invention.

FIELD

[0002] The present invention generally relates to nuclear technologies, and more particularly, to methods and apparatuses for facilitating localized nuclear fusion reactions in deuterated metals enhanced by electron screening.

BACKGROUND

[0003] In hot fusion, deuterons possessing high kinetic energy (i.e., “hot” deuterons) collide and fuse. However, in practice, nearly all deuterons are elastically scattered off of the Coulomb barrier of the nucleus with which they collide. See particle interactions 100 of FIG. 1A and graph 110 of FIG. 1B. The principle impediment for nuclear fusion is the strong Coulomb repulsion between the nuclei at close proximity. Bare nuclei cannot practically be fused since the Coulomb barrier elastic scattering cross section (i.e., the interaction probability of the two deuterons that does not lead to nuclear fusion) at small

angles (e.g., less than 90°) is unbounded and the vast majority of scattering cross sections are very high, meaning that small angle scattering is highly preferred during interactions of two hot charged particles, such as deuterons. Large angle scattering (e.g., 90° or more) is significantly less frequent than small angle scattering, although such large angle scattering may enable subsequent quantum tunneling, leading to close proximity of the nuclei and strong force-mediated nuclear reactions.

[0004] In conventional hot fusion approaches, the Coulomb repulsion can be overcome by heating (typically of all of) the fuel to extremely high temperatures (e.g., ~ 20 keV, or 2×10^8 K, which is much greater than the interior temperature of the sun at 1.5×10^7 K). At this extreme temperature, the nuclei have sufficient energy to tunnel through the Coulomb barrier. However, the fuel also becomes an inherently unstable hot plasma that requires confinement (e.g., magnetic confinement) so as not to vaporize the reactor walls. Indeed, no known physical structure could withstand temperatures even a small fraction of those required in conventional hot fusion processes.

[0005] Several other process-specific physical mechanisms leading to losses also make practical hot fusion impossible to date. Additionally, hot fusion processes rely on interactions between charged alpha particles (i.e., the nuclear reaction products) and the charged fuel nuclei to maintain hot fuel. This is an extremely inefficient process for transferring kinetic energy between particles in comparison with the highly efficient energy transfer upon elastic collisions between uncharged particles (such as neutrons) and charged fuel nuclei. The fuel density in the most widely used experimental configuration, a Tokamak reactor, is also extremely low, further reducing the overall reaction rate per unit volume. Currently, confinement time and plasma temperature conditions have been

insufficient in both inertial confinement fusion (ICF) and magnetic confinement fusion (Tokamaks) in order to achieve positive power output. In other words, such reactors consume more energy than they produce.

[0006] In the pursuit to understand astrophysical processes involving fusion processes, studies have been performed directing deuteron beams into deuterated metal substrates. These studies have measured substantially increased reaction rates over gaseous targets at same energy levels. A key difference between the two experimental configurations is the screening of the Coulomb electrostatic barrier between the charged particles. The bound shell and free conduction electron clouds in the metal targets act to screen the positive ion charge, where the projectile deuteron (d) effectively sees a reduced electrostatic barrier, leading to effectively higher reaction cross sections for d-D fusion than for bare nuclei. The projectile is notated with lower case “d” and the target is notated with an upper case “D”. The community introduced the concept of screening potential U_e to increase the probability of quantum tunneling by a uniform negative shift $-U_e$ of the Coulomb barrier $U_C(r)$. Researchers have found that U_e ranging from ~25 eV for gaseous targets to ~50 eV for deuterated insulators and semiconductor targets, to much higher levels for metals such as beryllium (~180 eV) and palladium (~800 eV). Nuclear reactions within the confine of a metal lattice may also provide additional benefits by invoking alternative reaction processes, such as Oppenheimer-Phillips reactions at low deuteron energy levels that may lead to multiplication events and higher process efficiency.

[0007] There are many impediments to creating a net positive energy source from conventional hot fusion approaches, including, but not limited to, the extremely low

reaction cross sections (σ) in gaseous targets, lack of efficient screening of the Coulomb barrier leading to small angle dominance of all elastic interactions between nuclei, as well as an extremely low kinetic energy transfer rate between charged particles to keep the fuel nuclei hot, the lack of inherently useful multiplication processes via interactions with metal nuclei, and the extremely low density of the reacting fuel nuclei. Accordingly, an improved nuclear fusion approach may be beneficial.

SUMMARY

[0008] Certain embodiments of the present invention may provide solutions to the problems and needs in the art that have not yet been fully identified, appreciated, or solved by conventional nuclear processes and technologies. For example, some embodiments of the present invention pertain to methods and apparatuses for facilitating localized nuclear fusion reactions in deuterated metals enhanced by electron screening, the reliance on hot neutrons to efficiently transfer kinetic energy to fuel nuclei, and the utilization of nuclear interactions with metal lattice nuclei and other nuclei to further enhance the overall reaction rate via process multiplication of nuclear events with positive energy output.

[0009] Screening is effective not only to enhance nuclear tunneling, but also to increase the probability of Coulomb scattering at large angles, which is a requisite for efficient subsequent tunneling. A deuterated or tritated metal (e.g., high Z metals or even low Z metals, such as lithium deuteride (LiD)) may be used to create an environment where electrons are well screened (i.e., deep screening). The metal lattice provides both the electrons for deep screening and a molecular “cage” so the deuterons

themselves can be at a high density. An external source of x-rays or gamma rays may be utilized to enhance further deep screening within the metal lattice. The metal lattice is bombarded with neutrons from a neutron source that provides a desired rate of neutron production. Process multiplication events of the hot neutrons used to efficiently transfer kinetic energy for local heating of the nuclear fuel for subsequent reactions can be designed using materials such as LiD could photodisintegrate or otherwise distintigrate at sufficiently high energy levels, or other materials capable of participating in Oppenheimer-Phillips reactions with hot deuterons even at low energy.

[0010] In an embodiment, a method includes providing a deeply screened fuel source to enhance nuclear tunneling and to increase a probability of Coulomb scattering at angles of at least 90° , for example. The method also includes subjecting the deeply screened fuel source to energetic neutrons that are in a keV and/or MeV range.

[0011] In another embodiment, a system includes a LINAC, an x-ray device, or both. The system also includes a deeply screened deuterated and/or tritated fuel source. The LINAC, the x-ray device, or both, are configured to subject the deeply screened deuterated and/or tritated fuel source to x-rays and/or gamma rays, respectively, causing fusion reactions to occur in the deeply screened deuterated and/or tritated fuel source. In some embodiments,

[0012] In yet another embodiment, a method includes producing photo neutrons by photodisintegration of a deeply screened deuterated or tritated fuel source a LINAC, the LINAC additionally serving as an ionization source for creation of a deeply screened environment for efficient tunneling and scattering events.

[0013] In still another embodiment, an apparatus includes a deuterated and/or tritated fuel source. The apparatus also includes at least one radioactive material located within the deuterated and/or tritated fuel source, or sufficiently close thereto to provide a predetermined amount of energetic neutrons.

[0014] In another embodiment, an apparatus includes an envelope surrounding a deuterated metal.

[0015] In yet another embodiment, a method includes providing at least one radioactive material within a deuterated and/or tritated fuel source.

[0016] In still another embodiment, a method is configured to produce hot neutrons with an energy of at least 3 MeV and to provide a natural isotope of lithium, ^7Li , the hot neutrons reacting with the ^7Li , resulting in direct production of a neutron cluster, the neutron cluster then being capable of efficiently participating in further nuclear reactions with fuel and lattice elements.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] In order that the advantages of certain embodiments of the invention will be readily understood, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments that are illustrated in the appended drawings. While it should be understood that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings, in which:

[0018] FIG. 1A illustrates an interaction between two particles, such as between charged particles (i.e., deuterons) or between uncharged particles (i.e., neutrons) and charged particles (i.e., deuterons), illustrating various potential scattering paths and a scattering angle θ .

[0019] FIG. 1B is a general graph illustrating the probability of Coulomb elastic scattering between two charged particles as a function of the scattering angle. Interactions at small angles dominate, but do not lead to subsequent nuclear interactions that are possible at large scattering angle above 90° , for example.

[0020] FIG. 2 illustrates a portion of a deuterated metal lattice, according to an embodiment of the present invention.

[0021] FIG. 3A illustrates the first stage of a deep screened fusion process in which a hot neutron is being introduced into a deuterated metal lattice, according to an embodiment of the present invention.

[0022] FIG. 3B illustrates the second stage of the deep screened fusion process in which a high energy (hot) neutron is being scattered off a low energy (cold) fuel nuclei within the deuterated metal lattice, thus delivering kinetic energy from the neutron to the fuel nuclei, according to an embodiment of the present invention.

[0023] FIG. 3C illustrates the third stage of the deep screened fusion process in which the hot fuel deuteron scatters off the cold deuteron at a high scattering angle and is effectively screened to result in a nuclear tunneling reaction between the hot deuteron and the cold deuteron, according to an embodiment of the present invention.

[0024] FIG. 4 illustrates a comparison between a conventional hot fusion process and a deeply screened fusion process, according to an embodiment of the present invention.

[0025] FIG. 5 is a flow diagram illustrating a deeply screened fusion process with subsequent nuclear events leading to neutron multiplications, according to an embodiment of the present invention.

[0026] FIG. 6A illustrates a deeply screened nuclear reaction process that uses photo neutrons, according to an embodiment of the present invention.

[0027] FIG. 6B illustrates a deeply screened nuclear reaction process that uses a radioactive neutron source, according to an embodiment of the present invention.

[0028] FIG. 7A is a side view illustrating a linear accelerator (LINAC)-based experimental example, according to an embodiment of the present invention.

[0029] FIG. 7B is a top view illustrating the cave of the experimental example with the top of the cave removed, according to an embodiment of the present invention.

[0030] FIG. 7C is a magnified side view of the experimental example illustrating the close proximity of the sample vials relative to the braking target, according to an embodiment of the present invention.

[0031] FIG. 8 shows a general architecture of the experimental setup, according to an embodiment of the present invention.

[0032] FIG. 9 is a graph illustrating the Bremsstrahlung photon spectrum for an electron beam endpoint of 2.9 MeV for a 450- μ A (per vial) test case (top of sample), according to an embodiment of the present invention.

[0033] FIG. 10A provides an example Pulse Shape Discrimination (PSD) plot relating PSD parameters versus electron equivalent energy recorded in the detector (EJ309 HV) for TS1576 ErD₃, according to an embodiment of the present invention.

[0034] FIG. 10B is a graph illustrating the EJ309 detector results for TS1576 (fueled, black line above) and TS589 (unfueled, dark gray line below) in detector counts (PMT counts after filtered using the process noted earlier) versus electron energy equivalent units (keVee), according to an embodiment of the present invention.

[0035] FIG. 10C is a graph illustrating the net counts (TS1576 (fueled) minus TS589 (unfueled) prior to unfolding with the HEBROW algorithms.

[0036] FIG. 11A is a graph illustrating neutron spectra for TS1575 (6-hours EJ309) net neutron counts (beam: 2.9 MeV, 15 mA), according to an embodiment of the present invention.

[0037] FIG. 11B is a graph illustrating neutron spectra for TS1576 (6-hours EJ309) net neutron counts (beam: 2.9 MeV, 15 mA), according to an embodiment of the present invention.

[0038] FIG. 11C is a graph illustrating neutron spectra for TS1575 (6-hours Stilbene) net neutron counts (beam: 2.9 MeV, 15 mA), according to an embodiment of the present invention.

[0039] FIG. 12 is a graph illustrating neutron spectra for TiD₂ (TS610-612) (5.5-hours EJ309) net neutron counts (Beam: 2.9 MeV, 15 mA), according to an embodiment of the present invention.

[0040] FIG. 13 is a flowchart illustrating deeply screened fusion reaction process, according to an embodiment of the present invention.

[0041] FIG. 14 is an architectural diagram illustrating a fusion reaction system, according to an embodiment of the present invention.

[0042] FIG. 15 is a block diagram illustrating a computing system configured to control a nuclear reaction rate, according to an embodiment of the present invention.

[0043] Unless otherwise indicated, similar reference characters denote corresponding features consistently throughout the attached drawings.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0044] Some embodiments of the present invention pertain to methods and apparatuses for facilitating localized nuclear fusion reactions in deuterated metals enhanced by electron screening. As used herein, the terms “deuteron” or “deuterated” may also refer to a “triton” or “tritated”, respectively. It was theorized that combining various or all features contributing to electron screening (e.g., lattice, shell, and Debye/plasma screening) into an enhanced screening energy U_e and utilizing the concept of an enhancement factor $f(E)$ to relate bare cross sections to those experimentally observed could be defined as follows. The experimental fusion cross section $\sigma_{exp}(E)$ can be written as:

$$\sigma_{exp}(E) = \sigma_{bare}(E) \cdot f(E) \quad (1)$$

[0045] where E is the projectile energy and $\sigma_{bare}(E)$ is the nuclear fusion cross section of bare nucleus ions. The enhancement factor $f(E)$ can be formulated as:

$$f(E) = \frac{S(E + U_e)}{S(E)} \cdot \frac{E}{(E + U_e)} \cdot \exp\{G(E) - G(E + U_e)\} \quad (2)$$

[0046] where $G(E)$ is the Gamow factor and $S(E)$ is the astrophysical factor.

[0047] From the theoretical analysis provided in detail below, electron screening (also referred to herein as “screening”) is effective not only to enhance nuclear tunneling, but also to increase the probability of Coulomb scattering at large angles. Without screening, low angle scattering of hot projectiles dominates, resulting in nonproductive elastic scattering and reduced tunneling. Therefore, efficient electron screening is a necessary ingredient for inducing and sustaining of nuclear fusion.

[0048] In particular, in some embodiments, the metal lattice nuclei of the deuterated material participate in a type of nuclear reaction called an Oppenheimer-Phillips process, in which charge polarization of the hot deuteron occurs when it approaches the target nucleus (e.g., the lattice metal nuclei). During the Oppenheimer-Phillips process, the proton-side faces away from the target nucleus and the neutron-side faces towards the target. A fusion reaction then ensues when the binding energy of the neutron and the target nucleus exceeds the binding energy of the deuteron. Depending on the energy of the incoming deuteron, either the proton or the neutron may fuse, although the neutron is typically absorbed, and a proton is then repelled from the transmuted nucleus. Both cases may lead to process multiplication, with the hot neutron being ejected off the target nucleus, providing a significant fraction of its kinetic energy to a nearby cold deuteron to continue the reaction process. Alternatively, a hot proton may either directly break down a deuteron or a metal lattice nucleus (e.g., a lithium nucleus), further resulting in additional hot neutrons or production of hot deuteron or tritium nuclei to enable subsequent nuclear processes.

[0049] From the theoretical analysis below, it is also evident that an optimal way to exchange kinetic energy between particles should involve uncharged particles.

Neutrons have relatively high scattering cross sections on nuclear fuel (e.g., deuterons), and can deliver a substantial portion of their kinetic energy in a single elastic collision to the deuteron. A fusion process was therefore examined in which kinetic energy exchange by hot neutrons to the fuel provides the basis for process initiation and potential secondary nuclear events.

[0050] A deuterated or tritated metal (e.g., lithium deuteride (LiD)) may be used to create an environment where electrons are well screened (i.e., deep screening). In certain embodiments, LiD is used with a sufficiently high photon energy to photodissociate the lithium, resulting in production of hot tritium or deuterons. A portion of such a deuterated metal lattice 200 is shown in FIG. 2. It should be noted that the metal may be one or more of lithium, boron, beryllium, a high Z metal, etc. In other words, different deuterated and/or tritated metals may be included in the metal lattice of FIG. 2. The metal lattice provides both the electrons for deep screening and a “cage” so the deuterons themselves can be at a high density and may further participate in reactions subsequent to the primary fusion reaction via multiple routes.

[0051] The metal lattice is bombarded with neutrons from a neutron source that provides a desired rate of neutron production. See, for example, step 300 of FIG. 3A. In FIG. 3A, two deuterons are contained within a metal lattice. A hot neutron travels towards the right deuteron in the lattice.

[0052] In step 310 of FIG. 3B, the hot neutron strikes the rightmost of the two deuterons, imparting energy on that deuteron and making it hot. Only uncharged particles, such as neutrons, may efficiently deliver significant amounts of their kinetic energy in a single elastic collision to a charged deuteron. For example, Table I below

provides the scattering cross section and the kinetic energy transfer between various particles, such as light, heavy charged particles, and neutrons, off deuterons at various levels of energy. Only the neutron can deliver a substantial portion of its kinetic energy to the deuteron, while all other charged interactions result in a small amount of kinetic energy being transferred. Therefore, only a deuteron that is heated by elastic collision with a hot neutron may possess sufficient kinetic energy to participate in subsequent nuclear tunneling reactions, whereas all other charged interactions result in only miniscule heating of the deuteron that cannot result in subsequent tunneling.

TABLE I: RESULTING DEUTERON ENERGIES FOR REACTIONS SHOWING PRIMACY OF NEUTRONS FOR ENERGY TRANSFER

Reaction (particle,D):	Cross Section σ (barns):	Resulting Average Deuteron Energy (eV):
Light Particles (e^- , e^+) $E_e = 2$ MeV	38.41 kb	24.75 meV
Heavy Particles: $E_p = 3$ MeV	5.76 Mb	41.4 meV
$E_d = 3$ MeV	11.51 Mb	42.7 meV
$E_\alpha = 3$ MeV	91.48 Mb	44 meV
Compton γ $E_\gamma = 2$ MeV	49.43 nb	2.13 keV
Neutron $E_n = 2.45$ MeV	3 b	1.09 MeV

[0053] As such, and unlike conventional fusion processes, only one of the two deuterons is heated in this example. This sends the hot deuteron towards the cold deuteron on the left, the screened Coulomb barrier of which is represented with a crescent shape. In this context, “cold” means kinetic energy measured in milli-electron volts (meV), corresponding to thousands of degrees Celsius or less. In contrast, “hot” means kinetic energy is much higher, e.g., as measured in the kilo-electron volt (keV) or mega-electron volt (MeV) range, corresponding to millions of degrees. In step 320

of FIG. 3C, the hot deuteron collides with the cold deuteron, and if the scattering angle is sufficiently large (e.g., greater than or equal to 90°), could subsequently tunnel through the Coulomb barrier of the cold deuteron via quantum tunneling. Because the right deuteron is hot, the probability of tunneling is relatively high. Both the probabilities of scattering at large angles and tunneling increase with electron screening.

[0054] The scattering probability between the neutron and the hot deuteron in such embodiments is much higher than in conventional hot fusion techniques. The neutron parts with a significant portion of its kinetic energy to the hot deuteron such that the latter can tunnel through the electrostatic barrier of another, much cooler deuteron and fuse therewith. Indeed, deep screening works very well if one of the deuterons is orders of magnitude cooler than the other.

[0055] This significantly differs from conventional hot fusion reactors, such as Tokamaks, for example. In a Tokamak, the entire fuel is ionized to hundreds of millions of degrees, but the fuel ions are only poorly screened by the hot plasma electrons. Hot deuterons are elastically scattered off the Coulomb barrier at small angles. This causes the probability that they will scatter away rather than potentially enable subsequent fusion to be very low. Fusion is enabled when deuterons strike one another at large angles (e.g., 90° or more), but this is rare and the tunneling probability is very small. Because a large volume of hot fuel is kept in place within the Tokamak, fusion does occur, in spite of the very low fuel plasma density and dominance of the non-productive low angle Coulomb elastic scattering. However, cooling through the reactor walls and additional losses through Bremsstrahlung radiation also occurs, and a tremendous

amount of energy is required to heat, maintain, and contain the fuel – indeed, more than is produced by the Tokamak process.

[0056] A key insight of some embodiments is that if the deuterons are highly screened by electron screening, the probability that fusion will occur becomes much larger. For instance, the probability may improve from one in a trillion in a Tokamak to one in millions or even one in thousands in some embodiments, depending on how deep (i.e., effective) the screening is in the deuterated or tritated metal. Screening increases the 90-180° Coulomb scattering angle chance, as well as the chance that hot deuterons will tunnel once they scatter in such large angles to begin with. Indeed, outside the so called “screening length,” the hot and cold deuterons cannot feel their mutual electrostatic repulsion, and thus in a deep screening case, the two nuclei can approach sufficiently close to one another to allow for nuclear tunneling and subsequent strong force fusion to occur. In the above description, the screening length is a convenient parameter to estimate the extent at which the electrostatic field is felt by other charged particles. The screening length could be estimated and derived for several cases of interest, such as for the case of screening by shell or conduction electrons or plasma electrons created by Compton scattering of gamma photons provided externally to the reacting volume.

[0057] With a rate of 1 billion neutrons per second and subsequent process multiplication events via Oppeneheimer-Phillips and other reaction processes, e.g., with LiD as the metal lattice/fuel configuration, leading to, e.g., 10^{14} nuclear events per second or tens or hundreds of watts in energy output, and with a metal lattice containing, e.g., a density of 10^{22} deuterons, there are still 10^8 seconds of power output, providing

for a long duration power source. As such, the reactions are highly localized and only occur sporadically in the deuterated metal lattice. However, a relatively small number of reactions are occurring continuously. This causes the deuterated metal lattice to stay relatively cool since the nuclear reaction heat produced locally is able to be dissipated through conduction and other means to the surroundings and not result in melting of the deuterated metal lattice as a whole unless neutrons are emitted at a high enough rate to cause melting, which can be controlled. While the local lattice may melt, conduction carries away the heat, the metal lattice and embedded fuel solidifies, and the surrounding molecules become relatively cool again.

[0058] In certain embodiments, a high-pressure gaseous fuel is provided to surround the deuterated metal. Such high pressure could be measured in the tens of thousands of pounds per square inch, leading to fuel density in the gaseous state to approximate that within the metal lattice. This high-pressure gas could participate in nuclear reactions as well. Alternatively, deuterium gas at pressure corresponding to that which is used to load and maintain the high fuel/lattice stoichiometry could be provided to ensure reloading of the lattice following resolidification of the lattice following localized nuclear reactions that lead to localized heating and melting.

[0059] Embodiments employing such a process provide complete control over the amount of energy that is produced since the number of neutrons that are delivered can be controlled. Also, if the neutron supply is shut off, the reactions stop. As such, the process is subcritical. Furthermore, the supply of neutrons can be controlled to throttle power production up or down. Neutrons are used in some embodiments as a key process mediator, efficiently heating of fuel nuclei and their products. Management of neutrons

in such embodiments via direct control of their input rate into the reacting volume, as well as their leakage from the same, is a key distinction of such embodiments from other hot fusion processes that rely on highly inefficient charged particle (e.g., alpha) heating to sustain the process.

[0060] Such embodiments also provide an element of safety over conventional nuclear reactors. For instance, if the reactor of some embodiments is employed on a satellite, and a rocket intended to carry the satellite into orbit explodes during launch, no nuclear reactions occur since the nuclear fuel may be totally radioactively inert to begin with (e.g., deuterium). Once in orbit, a device such as linear accelerator could be utilized to generate gamma radiation of sufficient energy above the photodisintegration limit of the deuteron (at 2.226 MeV) to yield hot neutrons to start the process of the employed embodiment. However, some embodiments do use radioactive elements (e.g., Californium, Americium, thorium, or any other suitable actinide) as a continuous neutron source to produce hot neutrons in the MeV range. Naturally, the number of neutrons emitted per second decreases over time as the element decays. Nevertheless, the process is well positioned for a compact, long duration, zero maintenance heat source which could then also be converted to electrical output using thermoelectric, Sterling, or other known heat to electrical conversion processes and devices.

[0061] The reaction rate R (e.g., the number of reactions per second per cm^3) is given by:

$$R \sim n_1 n_2 \sigma v \quad (3)$$

[0062] where n_1 and n_2 are fuel densities (e.g., particles per cm^3) of neutrons and deuterons, respectively, σ is the reaction cross section, and v is the kinetic energy. A

comparison 400 between a conventional hot fusion process and the deeply screened fusion process of some embodiments is shown in FIG. 4.

[0063] For σ to be high, a large angle of scattering plus subsequent tunneling is required. However, σ is relatively low in hot fusion, typically measured in milli-barns or below. Furthermore, in hot fusion, the plasma is about one million times less dense than the deuterium of some embodiments. In other words, hot fusion plasma is extremely rarified. Hot fusion reactors such as Tokamaks still achieve fusion due to a very high reactant volume, and all reactants are very hot. A Tokamak is designed for very large power outputs, whereas some embodiments of the present invention may be designed to produce lower levels of power, e.g., 100 watts, 1,000 watts, etc. These embodiments may have useful lifetimes of 20 to 30 years or more without being touched. Furthermore, in embodiments of the present invention, one reactant is hot whereas the other is relatively cool.

[0064] FIG. 5 is a flow diagram 500 illustrating a deeply screened fusion process, according to an embodiment of the present invention. A neutron source (natural or photo) inputs hot neutrons (1-n) into a deuterated lithium fuel. A “*” denotes a hot particle herein. The initial reactions between the hot neutrons (n) and the deuterons (d) or lithium, or between hot deuterons (d*), create He-3, alpha particles, and tritium (T). The output of the first pass is two hot alpha particles, two hot protons, two hot neutrons, and heat. As further shown, the simple combination of LiD (naturally containing both Li-6 and Li-7 isotopes) may result in a process that produces more neutrons per cycle. Since neutrons may effectively escape the reaction volume and participate in other processes not conducive for nuclear reactions, the entire net output of such an example

multiplication process depends on effective management of neutrons and their interactions with the surroundings.

[0065] FIG. 6A illustrates a deeply screened nuclear reaction process 600 that uses photo neutrons, according to an embodiment of the present invention. Photo neutrons are produced by photodisintegration of the deuterium fuel by gamma radiation produced via a linear accelerator (LINAC), which also serves as an ionization source for creation of a deeply screened environment for efficient tunneling and scattering events in some embodiments. The hot photo neutrons are sent into a deuterated fuel (e.g., deuterium contained within lithium, boron, beryllium, high Z metals or other materials capable of being deuterated, etc.), which is located within a beryllium neutron reflector and source. Fusion reactions (and other reactions) then occur as shown and described in FIGS. 3A-5.

[0066] FIG. 6B illustrates a deeply screened nuclear reaction process 610 that uses a radioactive neutron source, according to an embodiment of the present invention. Hot neutrons are emitted by a radioactive material (e.g., Californium, Curium, etc.). An x-ray device provides an ionization source for deep screening. The x-rays are sent into the radioactive material, which is located within a deuterated fuel (e.g., deuterium contained within lithium, boron, beryllium, etc.). The deuterated fuel, in turn, is located within a beryllium neutron reflector and source. Fusion reactions (and other reactions) then occur as shown and described in FIGS. 3A-5.

[0067] In some embodiments, a nuclear active process is employed that combines activation via the introduction of hot neutrons into a high-density deuteron environment within a metal lattice that may optionally include high Z elements in combination with,

or including, lithium, boron, or other elements. The hot neutrons efficiently heat the cold deuterons via elastic collisions, and the hot deuterons are deeply screened from other deuterons or from the lattice nuclei by a combination of shell or conduction electrons, or by Compton electrons produced by optionally irradiating the deuterated material via x-rays or gamma rays. The large angle scattering and nuclear tunneling probabilities of the hot deuteron with other deuterons or from the lattice nuclei is increased by the deep screening. Hot neutrons are generated by fusion of the hot and cold deuterons, secondary fusion reactions (e.g., with He-3 or tritium generated from a primary D-D reaction and other subsequent reaction products), Oppenheimer-Phillips reactions, other nuclear reactants generated by breaking down of deuterons or lithium, and/or related secondary processes leading to multiplication of nuclear events. In certain embodiments, a system includes deuterated metal, a hot neutron source generated via a gamma source of sufficient energy to photodisintegrate a deuteron or via natural decay processes of radioactive isotopes, and optionally, additional material capable of participating in multiplication processes including, but not limited to, lithium and an external envelop including beryllium or actinide nuclei, such as natural uranium, thorium, etc., to reflect or participate in nuclear reactions, or manage the neutron balance and kinetic energy thereof.

[0068] THEORETICAL ANALYSIS

[0069] Electron screening is essential for efficient nuclear fusion reactions to occur. Screening effects on fusion reaction rates as measured in deuterated materials have been demonstrated to be important. The nuclear reaction rate takes into account two primary events: (1) the Coulomb scattering of the projectile nuclei on the target nuclei; and (2)

nuclei tunneling through the Coulomb barrier. During elastic scattering of charged projectiles on target nuclei, such as a deuterons, some of the energy of the projectile particle is transferred to the target nucleus, thus heating it. Depending on the projectile particle energy and the efficiency of kinetic energy transfer during the scattering event, the target deuteron may become energetic enough to enable subsequent nuclear fusion reactions via tunneling through the Coulomb barrier of another atom's nucleus. Electron screening could play a significant role in this chain due to hot fuel interacting with lattice nuclei in the highly screened environment, as has been demonstrated in the experiments discussed above. This analysis focuses on analyzing the electron screening effect on Coulomb scattering and the tunneling process involving charged projectiles and the efficiency of kinetic energy transfer by charged and uncharged projectile particles on the target nucleus.

[0070] The nuclear fusion reactions in high density hydrogen isotopes (fuel) embedded in metal lattices are examined, when a small fraction of fuel nuclei is heated by energetic photo neutrons. Such a setup supports enhanced screening of the Coulomb barrier between fuel ions by conduction and shell electrons of the metal lattice. Electron screening significantly increases the probability of large versus small angle Coulomb scattering of the reacting nuclei to facilitate subsequent nuclear reactions via tunneling. This enhanced probability is integrated into the astrophysical factor $S(E)$.

[0071] Electron screening also increases the probability of fuel ions tunneling through the Coulomb barrier. Furthermore, screening significantly increases the probability of interaction between hot fuel and lattice nuclei due to Oppenheimer-Phillips processes, which could open potential routes to reaction multiplication. The

applicability of the electron screening potential energy U_e for the calculation of the enhancement factor $f(E)$ to the nuclear fusion cross section is examined. The expression of U_e is also derived for general screening process using a unifying concept of a screening length λ_{sc} . It was found that energetic neutrons provide the most effective heating of fuel ions to initiate nuclear fusion reactions in condensed matter, in comparison with heating via energetic charged particles. The above effects were integrated into an overall analysis of a nuclear fusion process that could be used as a theoretical basis for understanding, designing, and optimizing of experiments, such as those discussed above.

[0072] NUCLEAR FUSION WITH ELECTRON SCREENING

[0073] Per the above, electron screening is essential for efficient nuclear fusion reactions to occur.

[0074] A. NUCLEAR FUSION CROSS-SECTION OF BARE IONS

[0075] In the standard case of sub-barrier quantum tunneling through the Coulomb barrier between positive nucleus ions, the nuclear fusion cross-section of bare nucleus ions $\sigma_{bare}(E)$ can be written as:

$$\sigma_{bare}(E) = \frac{S(E)}{E} \cdot \exp(-G(E)) \quad (5)$$

[0076] where E is the energy in the center of mass (CM) reference frame and $S(E)$ is the astrophysical S -factor containing the details of nuclear interactions. In the non-relativistic case, the relation between energy E in the CM frame and the kinetic energy $K_{1\infty}$ of the projectile nucleus ion in the lab frame takes the relatively simple form:

$$K_{1\infty} \equiv \frac{m_1(\vec{v}_{1\infty})^2}{2} = \left(1 + \frac{m_1}{m_2}\right)E \quad (6)$$

[0077] A lab frame target nucleus ion with mass m_2 is at rest (i.e., $\vec{v}_2 = 0$) and the projectile nucleus ion with mass m_1 has a velocity of $\vec{v}_{1\infty}$ at infinity.

[0078] In Wentzel-Krammers-Brillouin (WKB) approximation, the Gamow factor $G(E)$ involves the evaluation of the following integral:

$$G(E) = \frac{2}{\hbar} \int_{r_0}^{r_{ctp}} [2\mu\{U_C(r) - E\}]^{1/2} dr \quad (7)$$

[0079] Here, \hbar is the reduced Planck constant, $U_C(r)$ is the Coulomb potential energy $U_C(r) = Z_1e \cdot Z_2e/r$ (the Coulomb barrier) of the projectile nucleus with charge Z_1e in the Coulomb field Z_2e/r of the target nucleus, $\mu = m_1m_2/(m_1 + m_2)$ is the reduced mass of the projectile and target nuclei, $r_0 = (R_1 + R_2)$ is the classical distance of closest approach with nuclei (effective) radii R_1 and R_2 , and r_{ctp} is the classical turning point, determined from the following expression:

$$E = U_C(r_{ctp}) \rightarrow r_{ctp} = \frac{(Z_1E)(Z_2E)}{E} \quad (8)$$

[0080] Evaluation of the integral in Eq. (7) gives the standard expression for the Gamow factor:

$$G(E) = \left(\frac{E_G}{E}\right)^{1/2} \cdot \left[\frac{2}{\pi} \left\{ \cos^{-1} \sqrt{\frac{E}{V_C}} - \sqrt{\frac{E}{V_C} \left(1 - \frac{E}{V_C}\right)} \right\} \right] \quad (9)$$

[0081] Where $V_C = (Z_1e)(Z_2e)/r_0$ is the full height of the Coulomb barrier, $E_G = 2\mu c^2(\pi\alpha Z_1Z_2)^2$ is the Gamow energy, and $\alpha = e^2/\hbar c$.

[0082] In the limit of $\sqrt{\frac{E}{V_C}} \ll 1$ (what is usually the case), the Gamow factor reduces to the RELATIVELY simple Sommerfeld expression:

$$G(E) = \left(\frac{E_G}{E}\right)^{1/2} \cdot \left(1 - \frac{4}{\pi} \sqrt{\frac{E}{V_C}} + \dots\right) \rightarrow \frac{E_G}{E} \quad (10)$$

[0083] B. COULOMB BARRIER SCREENING BY LATTICE ELECTRONS

[0084] In experiments with deuteron beams and deuterated targets, when target deuterium nuclei (d) were embedded in insulators and semiconductors, a relatively small enhancement of nuclear reaction rates was found for $d(d,p)t$ nuclear fusion reactions as compared to gaseous D_2 target experiments. These enhancements of reaction rates for $d(d,p)t$ nuclear reactions in host insulators and semiconductors is naturally explained by the screening of interacting nuclei by static electron clouds localized in atomic shells of host materials. Collectively, shell electrons produce a negative screening potential for the projectile nucleus, effectively reducing the height and spatial extension of the Coulomb barrier between interacting nuclei.

[0085] However, much larger effects have been readily measured with deuterated metal targets (excluding the noble metals, such as copper (Cu), silver (Ag), and gold (Au)). A large enhancement of the nuclear reaction rates for $d(d,p)t$ fusion reactions in host metals could be considered as the result of an additional dynamic screening by free moving conduction electrons, which are readily concentrated near the positive ions. These screening effects are collectively referred to as the “lattice screening.”

[0086] Electron screening of target nuclei either by atomic shell electrons or conduction electrons (usually both) can be approximated by a negative uniform shift $-U_e$ of the Coulomb barrier $U_C(r)$. The lowering of $U_C(r)$ by U_e is equivalent to the increase of E by U_e , as can be seen in Eq. (3) – namely, $\{U_C(r) - U_e\} - E = U_C(r) - \{E + U_e\}$. The uniform shift U_e is called the electron screening potential energy.

[0087] Therefore, the experimentally measured tunneling probability $\sigma_{exp}(E)$ in a screened target at the ion energy E in CM can be evaluated as the experimentally measured tunneling probability for bare ions collision at higher energy $(E + U_e)$:

$$\sigma_{exp}(E) \equiv \sigma_{screen}(E) = \sigma_{bare}(E + U_e) \quad (11)$$

[0088] The experimental fusion cross-section $\sigma_{exp}(E)$ can be written as:

$$\sigma_{exp}(E) = \sigma_{bare}(E) \cdot f(E) \quad (12)$$

[0089] (identical to Eq. (1) above), which is actually the definition of the enhancement factor $f(E)$.

[0090] From Eq. (5), the expression for the enhancement factor $f(E)$ can be found:

$$f(E) = \frac{S(E + U_e)}{S(E)} \cdot \frac{E}{(E + U_e)} \cdot \exp\{G(E) - G(E + U_e)\} \quad (13)$$

[0091] (which is identical to Eq. (2) above). In the case of $S(E + U_e)S(E)$, which is usually the case, the enhancement factor $f(E)$ can be written as:

$$f(E) = \frac{E}{(E + U_e)} \cdot \exp\{G(E) - G(E + U_e)\} \quad (14)$$

[0092] In the limit of $\sqrt{\frac{E}{v_c}} \ll 1$, Eq. (13) is further reduced to:

$$f(E) = \frac{E}{(E + U_e)} \cdot \exp\left\{\frac{U_e}{2E} \left(\frac{E_G}{E}\right)^{1/2}\right\} \quad (15)$$

[0093] As it follows from Eq. (10).

[0094] The experimental values for electron screening potential energies are $U_e = 25 \pm 15eV$ for gaseous targets and $U_e = 39$ to $52eV$ for deuterated insulators and semiconductors targets. However, for deuterated metal targets, much larger values of electron screening potential energies are measured, ranging from $U_e = 180 \pm 40eV$ for

beryllium to $U_e = 800 \pm 90\text{eV}$ for palladium. The exclusion is observed for deuterated noble metal targets, namely, $U_e = 43 \pm 20\text{eV}$ (Cu), $U_e = 23 \pm 10\text{eV}$ (Ag), and $U_e = 61 \pm 20\text{eV}$ (Au).

[0095] Theoretical values for U_e screening by localized, host atomic shell, static electron clouds calculated in the adiabatic limit from atomic binding energies, correlate well with experimentally measured values for U_e for gaseous targets, as well as for deuterated insulators and semiconductors targets. In contrast, the theoretically calculated static electron cloud U_e screening potential energies of host metal atomic shells are almost one order of magnitude smaller than values of electron screening potential energies U_e experimentally measured for deuterated alkaline metal targets. These discrepancies require a different physical mechanism for theoretical understanding of the experimental results. This requires a novel physical mechanism involving quasi-free-moving conduction electrons in metals as an additional source for screening of interacting nuclei.

[0096] C. EVALUATION OF THE ELECTRON SCREENING POTENTIAL ENERGY

[0097] The effect of electron screening could be straightforwardly estimated by recalculating the Gamow factor $G(E)$ in Eq. (7) by replacing the Coulomb potential energy $U_C(r) \rightarrow U_{C,sc}(r)$ with the general expression for the screened Coulomb potential energy $U_{C,sc}(r)$:

$$U_{C,sc}(r) = \frac{Z_1 e \cdot Z_2 e}{r} \cdot \exp\left(-\frac{r}{\lambda_{sc}}\right) \quad (16)$$

[0098] where λ_{sc} is the corresponding screening length, which is described in further detail later on herein. The radial distance r in Eq. (7) is less than or equal to the classical

turning point r_{ctp} , given by Eq. (8), which, in turn, is generally much smaller than the characteristic distance of the electron cloud distribution from the reacting nuclei, the corresponding screening length λ_{sc} :

$$r_0 \leq r \leq r_{ctp} \ll \lambda_{sc} \quad (17)$$

[0099] Since $r \ll \lambda_{sc}$, we can expand $\exp\left(-\frac{r}{\lambda_{sc}}\right) = \left(1 - \frac{r}{\lambda_{sc}}\right)$ in Eq. (16) to find the screened Coulomb potential energy $U_{C,sc}(r)$ (the screened Coulomb barrier) as:

$$U_{C,sc}(r) = \frac{Z_1 e \cdot Z_2 e}{r} \cdot \exp\left(1 - \frac{r}{\lambda_{sc}}\right) = \frac{Z_1 e \cdot Z_2 e}{r} - \frac{Z_1 e \cdot Z_2 e}{\lambda_{sc}} = U_C(r) - U_e \quad (18)$$

[0100] with the standard Coulomb barrier $U_C(r)$:

$$U_C(r) = \frac{Z_1 e \cdot Z_2 e}{r} \quad (19)$$

[0101] and the electron screening potential energy U_e determined as:

$$U_e = \frac{Z_1 e \cdot Z_2 e}{\lambda_{sc}} \quad (20)$$

[0102] Therefore, the concept of an electron screening potential energy U_e , introduced above in Eqs. (11)-(15), could be theoretically justified if the classical turning point r_{ctp} is much smaller than the corresponding screening length λ_{sc} , the necessary condition, as stated in Eq. (17).

[0103] In the following we consider several cases for the electron screening length λ_{sc} generated by atomic shell electrons, by plasma particles (ions, electrons), by conduction electrons in metal matrix, or any combination thereof.

[0104] The modified (to better fit experimental data) Thomas-Fermi screening length λ_{TF} (atom size) by atomic shell electrons of host material is given by the following relation:

$$\lambda_{TF} = \frac{1.4 \cdot a_0}{Z^{1/3}} \quad (21)$$

[0105] where a_0 is the Bohr radius of $a_0 = 5.29 \cdot 10^{-9}$ cm and Z is the atomic number of the host material.

[0106] The Debye screening length λ_D in two component, two temperature plasma is given by the following expression:

$$\lambda_D^{-2} = \lambda_{Di}^{-2} + \lambda_{De}^{-2} \quad (22)$$

[0107] Where λ_{Di} and λ_{De} are the ion and electron Debye length, respectively. They are defined as:

$$\lambda_{Di} = \left(\frac{kT_i}{4\pi \cdot n_{i0} \cdot e^2} \right)^{1/2}, \lambda_{De} = \left(\frac{kT_e}{4\pi \cdot n_{e0} \cdot e^2} \right)^{1/2} \quad (23)$$

[0108] If the electron temperature T_e is much higher than ion temperature T_i (i.e., hot electrons versus cold ions), then the Debye screening length λ_D for two component two temperature plasma is determined by the ion Debye length λ_{Di} , namely:

$$T_e \gg T_i \rightarrow \lambda_D = \lambda_{Di} = \left(\frac{kT_i}{4\pi \cdot n_{i0} \cdot e^2} \right)^{1/2} \quad (24)$$

[0109] as it follows from Eq. (22) and Eq. (23). As a reference, accelerator deuteron experiments are characterized by hot electrons and hot deuterons, whereas deuterated metals offer an environment with hot electrons, but cold ions. This difference has significant consequences regarding the screening efficiency in these two types of experiments.

[0110] In order to explain theoretically the high values of electron screening potential U_e^{exp} , experimentally measured for deuterated alkaline metal targets, it has been suggested to take into account the presence of quasi-free-moving conduction

electrons in metals for screening of interacting nuclei. It has been considered there that differences between the Fermi-Dirac distribution of the conduction electrons and the classical (Boltzmann) distribution may be expected to be negligible for the electron screening at room temperature. In that simplified model, deuteron ions, together with metal conduction electrons, were treated as a one component equilibrium classical plasma including metallic, quasi-free-moving conduction electrons (providing plasma screening) and singly-charged localized deuteron ions (not contributing to plasma screening). The Debye screening length in a one component equilibrium ($T_e = T_i$) classical (Boltzmann) plasma, approximating the screening length by conduction electrons $\lambda_{De,c}$, reduces to the electron Debye screening length λ_{De} :

$$\lambda_{De,c} = \lambda_{De} = \left(\frac{kT_e}{4\pi \cdot n_{e0} \cdot e^2} \right)^{1/2} \quad (25)$$

[0111] The electron screening potential U_e is entangled in an enhancement factor $f(E)$ given by Eq. (13)-(15), which factorizes the collisional fusion cross-section for bare ions $\sigma_{bare}(E)$ in order to obtain the screened fusion cross-section $\sigma_{screen}(E)$:

$$\sigma_{exp}(E) = \sigma_{screen}(E) = \sigma_{bare}(E) \cdot f(E) \quad (26)$$

[0112] as expressed by Eq. (12) for the measured experimental fusion cross-section $\sigma_{exp}(E)$.

[0113] The general case, taking into account possible simultaneous screening of reacting hydrogen isotope nuclei by host atomic shell electrons, conduction electrons, and plasma electrons, finds the total screening potential energy $U_{e,sc}$, estimated as:

$$U_{e,sc} = \frac{e^2}{\lambda_{sc}} \quad (27)$$

[0114] where the screening length λ_{sc} is given by following general relation:

$$\lambda_{sc}^{-2} = \lambda_{TF}^{-2} + \lambda_{De,c}^{-2} + \lambda_D^{-2} \quad (28)$$

[0115] where λ_{TF} is the modified Thomas-Fermi screening length by atomic shell electrons of the host material, $\lambda_{De,c}$ is the screening length by conduction electrons, and λ_D is the Debye screening length by ions in classical plasma.

[0116] Since the inverse square of screening lengths λ_{TF}^{-2} , $\lambda_{De,c}^{-2}$, or λ_D^{-2} is proportional to the corresponding electron number density, the derivation of Eq. (28) is similar to the derivation of Eq. (22). A summation of electron number densities was used for both where the total charge density is represented by the electrostatic Poisson's equation for the screened Coulomb interaction potential.

[0117] D. NUMERICAL EXAMPLES FOR THE ENHANCEMENT FACTOR $f(E)$

[0118] In this section, the derivations above are applied to calculate enhancement factors $f(E)$, determined by Eq. (14), for the reactions (d, D) (top – in ErD_3), $(d, {}^{166}\text{Er})$ (middle – in ErD_3 with 100-140 keV projectile energy), and $(d, {}^{110}\text{Pd})$ (bottom – in a Pd-D matrix), shown in graphs XX00 of FIG. XX. More specifically, FIG. XX shows calculated enhancement factors $f(E)$ in deuterated metals versus deuteron projectile energy.

[0119] REACTION (d, D)

[0120] For the projectile and target nuclei are both deuterons (i.e., $m_1 = m_d$, $m_2 = m_d$, and $Z_2 = Z_1 = 0$), $U_e = e^2/\lambda_{sc}$, according to Eq. (20).

[0121] REACTION $(d, {}^{166}\text{Er})$ OPPENHEIMER-PHILLIPS

[0122] For the projectile nucleus being a deuteron and the target nucleus being ^{166}Er (i.e., $m_1 = m_d, m_2 = m_{^{166}\text{Er}}$, and $Z_1 = 1, Z_2 = 68$), $U_e = 68e^2/\lambda_{sc}$, according to Eq. (20).

[0123] REACTION ($d, ^{110}\text{Pd}$)

[0124] For the projectile nucleus being a deuteron and the target nucleus being ^{110}Pd (i.e., $m_1 = m_d, m_2 = m_{^{110}\text{Pd}}$, and $Z_1 = 1, Z_2 = 110$), $U_e = 110e^2/\lambda_{sc}$, according to Eq. (20).

[0125] It can be seen that there is a sharp rise in the enhancement factor $f(E)$ for deuterium interaction with host metals, especially at low deuteron energies. These enhancement factors at low deuteron energies may be resulting in the screened deuteron interaction of interest, as discussed in the experimental section above.

[0126] COULOMB SCATTERING ON TARGET NUCLEI

[0127] Coulomb scattering of energetic projectile particles on target nuclei is the principle process associated with the nuclear interactions of interest. Fusion nuclear events significantly favor large-angle scattering in order to bring reacting ions to the classical distance of closest approach, significantly increasing the likelihood of tunneling through the Coulomb barrier. However, small angle elastic scattering dominates Coulomb scattering interactions under normal, unscreened conditions. Generally, electron screening while reducing the Coulomb barrier can significantly reduce the small-angle elastic scattering, thus increasing the probability of large-angle scattering and enhancing nuclear fusion reactions rates. Elastic scattering of energetic projectiles on target nuclei are analyzed herein, including the effects of electron screening by plasma electrons, as well as by conduction electrons in deuterated metals.

As for the kinetic energy transfer from projectile to target nuclei, it was found that the kinetic heating of fuel nuclei is most efficient by energetic neutral particles, such as neutrons and γ -quanta.

[0128] A. LIGHT PARTICLES (e^- , e^+) ELASTIC COULOMB SCATTERING

[0129] The Coulomb scattering of relativistic projectile electrons on target atoms is characterized by the projectile electron-target atom differential cross section $d\sigma/d\Omega|_{e-a}$, which is determined as the sum of the projectile electron-target nucleus differential cross-section $d\sigma/d\Omega|_{e-N}$ and the projectile electron-target orbital electron differential cross section $d\sigma/d\Omega|_{e-e}$ multiplied by Z (the atomic number of target atoms), and is given by the following relation:

$$\frac{d\sigma}{d\Omega}|_{e-a} = \frac{d\sigma}{d\Omega}|_{e-N} + Z \cdot \frac{d\sigma}{d\Omega}|_{e-e} = \frac{D_{e-a}^2 \cdot \left(1 - \frac{\beta^2}{2} \cdot (1 - \cos \theta)\right)}{(2 \cdot (1 - \cos \theta) + \theta_{min}^2)^2} \quad (29)$$

[0130] where θ is the electron scattering angle, $\beta = v_e/c$ (where v_e is the velocity of the projectile electron and c is the speed of light), and θ_{min} is the atomic screening parameter defined as:

$$\theta_{min} = \frac{\hbar/\lambda_{TF}}{p_e} \quad (30)$$

[0131] where \hbar is the reduced Planck constant and λ_{TF} is the modified Thomas-Fermi target atomic radius given by Eq. (21). The electron momentum p_e is determined by the following relations:

$$p_e = \frac{E_e}{c} \cdot \left(1 + \frac{2m_e \cdot c^2}{E_e}\right)^{\frac{1}{2}}, p_e \cdot c = E_e \cdot \left(1 + \frac{2m_e \cdot c^2}{E_e}\right)^{\frac{1}{2}} \quad (31)$$

[0132] where $E_e = E_e - m_e \cdot c^2$ is the kinetic energy of the projectile electron (E_e is the total energy of projectile electron and m_e is the electron mass).

[0133] Eq. (29) was derived in the first Born approximation to the Dirac equation for the Wentzel-Thomas-Fermi screened Coulomb atomic potential (energy):

$$V_{C,sc}(r) = \frac{e \cdot (Z \cdot e)}{r} \cdot \exp\left(-\frac{r}{\lambda_{TF}}\right) \quad (32)$$

[0134] The projectile electron-target atom elastic scattering characteristic distance D_{e-a} is determined from the following relation:

$$D_{e-a}^2 = D_{e-N}^2 + (Z \cdot D_{e-e})^2 \quad (33)$$

[0135] where the projectile electron-target nucleus characteristic scattering distance D_{e-N} is determined by:

$$D_{e-N} = \frac{Z \cdot e^2}{\gamma \cdot m_e \cdot (v_e^2/2)} = \frac{2Z \cdot r_e \cdot \sqrt{1 - \beta^2}}{\beta^2} = \frac{Z \cdot e^2}{\beta \cdot E_e \cdot (1 + (m_e c^2/E_e))^{1/2}} \quad (34)$$

[0136] with $\gamma = 1/\sqrt{1 - \beta^2}$. The projectile electron-target orbital electron characteristic scattering distance D_{e-e} is given by:

$$D_{e-e} = \frac{e^2}{\gamma \cdot m_e \cdot (v_e^2/2)} = \frac{2r_e \cdot \sqrt{1 - \beta^2}}{\beta^2} = \frac{2e^2}{\beta \cdot E_e \cdot (1 + (m_e c^2/E_e))^{1/2}} \quad (35)$$

[0137] Here, $r_e = e^2/m_e c^2$ is the classical radius of electron $r_e = 2.82$ femtometers (fm) = 2.82×10^{-13} cm. Substitution of Eqs. (34) and (35) into Eq. (33) yields:

$$D_{e-a} = \frac{2r_e \cdot \sqrt{Z(Z+1)}}{\gamma \cdot \beta^2} = \frac{2e^2 \cdot \sqrt{Z(Z+1)}}{\beta \cdot E_e \cdot (1 + (m_e c^2/E_e))^{1/2}} \quad (36)$$

[0138] The total cross section σ_{e-a} for a single scattering event is obtained by integrating the differential cross section for projectile electrons scattering over $d\Omega$ on target atoms from Eq. (29):

$$\begin{aligned}\sigma_{e-a} &= \int \left. \frac{d\sigma}{d\Omega} \right|_{e-a} d\Omega \\ &= \frac{\pi D_{e-a}^2}{\theta_{min}^2} \cdot \left(\left(\frac{4 + \beta^2 \theta_{min}^2}{4 + \theta_{min}^2} \right) - \frac{\beta^2 \theta_{min}^2}{4} \cdot \ln \left(\frac{4}{\theta_{min}^2} - 1 \right) \right) \quad (37)\end{aligned}$$

[0139] where θ_{min} is given by Eq. (30), $\theta_{min} = (\hbar/p_e) \cdot \lambda_{TF}^{-1}$.

[0140] The expression for σ_{e-N} follows from Eq. (37) with the substitution $D_{e-a}^2 \rightarrow D_{e-N}^2$:

$$\begin{aligned}\sigma_{e-N} &= \int \left. \frac{d\sigma}{d\Omega} \right|_{e-N} d\Omega \\ &= \frac{4\pi e^4 \cdot \lambda_{TF}^2}{\hbar^2 c^2 \beta^2} \\ &\quad \cdot \left(\left(\frac{4 + \beta^2 \theta_{min}^2}{1 + \theta_{min}^2} \right) - \frac{\beta^2 \theta_{min}^2}{4} \cdot \ln \left(\frac{4}{\theta_{min}^2} - 1 \right) \right) \quad (38)\end{aligned}$$

[0141] For $E_e = 2$ MeV and $m_N = m_d$ (deuteron mass), the numerical value for σ_{e-d} is as follows:

$$\sigma_{e-d} = \int \left. \frac{d\sigma}{d\Omega} \right|_{e-d} d\Omega \approx \frac{\pi D_{e-d}^2}{\theta_{min}^2} = \frac{4\pi e^4 \cdot \lambda_{TF}^2}{\hbar^2 c^2 \beta^2} = 38.41 \text{ knb} \quad (39)$$

[0142] since $\pi D_{e-d}^2 = 45.1 \text{ mbn}$, but $\theta_{min}^2 = (\hbar/p_e)^2 \cdot \lambda_{TF}^{-2} = 1.17 \times 10^{-6}$.

“kbn,” “mbn,” and Gbn are kilo-barns, milli-barns, and giga-barns, respectively, where a “barn” is the standard nuclear cross section metric of 10^{-24} cm^2 .

[0143] The target nucleus recoil energy can be found from the conservation of the total momentum in the elastic projectile electron-target nucleus scattering process:

$$\vec{p}_N = \vec{p}_e - \vec{p}'_e \quad (40)$$

[0144] Where \vec{p}_N is the target nucleus recoil momentum, \vec{p}_e is the momentum of incident electron, and \vec{p}'_e is the momentum of the scattered electron. Since in elastic scattering $p_e = |\vec{p}_e| \approx |\vec{p}'_e|$ (for the reason that small angle scattering is the most probable event), it follows from Eq. (40) that:

$$p_N^2 = \vec{p}_N^2 = \vec{p}_e^2 + \vec{p}'_e^2 - (2\vec{p}_e \cdot \vec{p}'_e \cdot \cos \theta) \approx 2p_e^2 \cdot (1 - \cos \theta) \quad (41)$$

[0145] where θ is the scattering angle. Correspondingly, the target nucleus recoil energy $E_N(\theta)$ follows from Eq. (41), with the help of Eq. (31):

$$E_N(\theta) = \frac{p_N^2}{2m_N} \approx \frac{p_e^2}{m_N} \cdot (1 - \cos \theta) = \frac{E_e^2}{m_N \cdot c^2} \left(1 + \frac{2m_e c^2}{E_e} \right) \cdot (1 - \cos \theta) \quad (42)$$

[0146] where $E_e = E_e - m_e c^2$ is the kinetic energy of projectile electron, E_e is the total energy of the projectile electron, and m_e and m_N are the electron and nucleus masses, respectively.

[0147] The mean target nucleus recoil energy \bar{E}_N in a single elastic projectile electron-nucleus (target) collision is obtained by the averaging of $E_N(\theta)$ over $d\Omega$:

$$\bar{E}_N = \frac{\int E_N(\theta) \cdot (d\sigma/d\Omega|_{e-N}) \cdot d\Omega}{\int (d\sigma/d\Omega|_{e-N}) \cdot d\Omega} \quad (43)$$

[0148] Substitution of $\frac{d\sigma}{d\Omega}|_{e-N}$ into Eq. (43) and taking the integral yields the expression for the mean target nucleus recoil energy \bar{E}_N in a single elastic projectile electron-nucleus (target) collision yields:

$$\bar{E}_N = \frac{\hbar^2}{m_N \cdot \lambda_{TF}^2} \cdot \frac{\left((2 + \alpha) \cdot (1 + \alpha \cdot \beta^2) \cdot \ln\left(\frac{2+\alpha}{\alpha}\right) - 2(1 + (1 + \alpha)\beta^2) \right)}{2(2 + \alpha \cdot \beta^2) - \alpha \cdot (2 + \alpha) \cdot \beta^2 \cdot \ln\left(\frac{2+\alpha}{\alpha}\right)} \quad (44)$$

[0149] where $\alpha = \theta_{min}^2/2$ and $\beta = v_e/c$. For $E_e = 2$ MeV and $m_N = m_d$ (deuteron mass), the numerical value for the mean target nucleus recoil energy $\bar{E}_N = \bar{E}_d$ in a single elastic projectile electron-target deuteron nucleus collision is as follows:

$$\bar{E}_d = 24.75 \text{ meV} \quad (45)$$

[0150] B. HEAVY PARTICLES ELASTIC COULOMB SCATTERING (d, p, α)

[0151] The Coulomb scattering of the heavy projectile particles on target nuclei is characterized by the heavy projectile particles-target nuclei differential cross section, which is given by Eq. (29) with the substitution $D_{e-a}^2 \rightarrow D_{p-N}^2$, namely:

$$\left. \frac{d\sigma}{d\Omega} \right|_{p-N} = \frac{D_{p-N}^2 \cdot \left(1 - \frac{\beta_p^2}{2} \cdot (1 - \cos \theta) \right)}{\left(2 \cdot (1 - \cos \theta) + \theta_{min,p}^2 \right)^2} \quad (46)$$

[0152] where $\beta_p = v_p/c$, and $\theta_{min,p}$ being equal to:

$$\theta_{min,p} = \frac{\hbar/\lambda_{TF}}{p_p} = \frac{\hbar/\lambda_{TF}}{\sqrt{2m_p \cdot E_p}} \quad (47)$$

[0153] where $p_p = \sqrt{2m_p \cdot E_p}$ is the projectile momentum and m_p and E_p are the projectile mass and kinetic energy, respectively.

[0154] The projectile particle-target nucleus characteristic scattering distance D_{p-N} is determined by:

$$D_{p-N} = \frac{z_p \cdot Z_N \cdot e^2}{E_p} \quad (48)$$

[0155] where z_p is the projectile particle atomic number ($z_p = 1$ for the proton and deuteron projectile, $z_p = 2$ for the α projectile), and Z_N is the target nucleus atomic number.

[0156] The total cross section σ_{p-N} for a single scattering event is obtained from Eq. (37) with the substitution $D_{e-a}^2 \rightarrow D_{p-N}^2$ and with $\beta \rightarrow \beta_p \ll 1$, since the heavy projectiles are nonrelativistic:

$$\sigma_{p-N} = \frac{\pi \cdot D_{p-N}^2}{\theta_{min,p}^2} \cdot \left(1 + \frac{\theta_{min,p}^2}{4}\right)^{-1} \rightarrow \frac{\pi \cdot D_{p-N}^2}{\theta_{min,p}^2} = \frac{2\pi \cdot m_p \cdot e^4 \cdot z_p^2 \cdot Z_N^2}{\hbar^2} \cdot \frac{\lambda_{TF}^2}{E_p} \quad (49)$$

[0157] since $\theta_{min,p} = (\hbar/(\lambda_{TF} \cdot p_p)) - 1$, $\lambda_{TF} = 1.4a_0 \cdot Z_N^{-1/3}$, $p_p = \sqrt{2m_p \cdot E_p}$.

[0158] In Eq. (49), σ_{p-N} could be written as $\sigma_{p-N} = \frac{S^{el}(E_p)}{E_p}$, where $S^{el}(E_p) = (2\pi \cdot m_p \cdot e^4 \cdot z_p^2 \cdot Z_N^2 \cdot \lambda_{TF}^2)/\hbar^2$ represents the elastic scattering component of the astrophysical factor.

[0159] For a proton projectile with $E_p = 3$ MeV and a deuteron target nucleus ($m_N = m_d$), the numerical value for σ_{p-D} (scattering) is as follows:

$$\sigma_{p-D} = \int \frac{d\sigma}{d\Omega} \Big|_{p-D} d\Omega \approx \frac{\pi \cdot D_{p-D}^2}{\theta_{min,p}^2} = \frac{2\pi \cdot m_p \cdot e^4}{\hbar^2} \cdot \frac{2\lambda_{TF}^2}{E_p} = 5.76 \text{ Mbn} \quad (50)$$

[0160] For a deuteron projectile with $E_d = 3$ MeV and a deuteron target nucleus ($m_N = m_d$), the numerical value for σ_{d-D} (scattering) is as follows:

$$\sigma_{d-D} = \int \frac{d\sigma}{d\Omega} \Big|_{d-D} d\Omega \approx \frac{\pi \cdot D_{d-D}^2}{\theta_{min,d}^2} = \frac{2\pi \cdot m_d \cdot e^4}{\hbar^2} \cdot \frac{2\lambda_{TF}^2}{E_d} = 11.51 \text{ Mbn} \quad (51)$$

[0161] whereas for deuteron projectile with $E_d = 10$ keV and a deuteron target nucleus ($m_N = m_d$), the numerical value for σ_{d-D} (scattering) is as follows:

$$\sigma_{d-D} = \int \left. \frac{d\sigma}{d\Omega} \right|_{d-D} d\Omega \approx \frac{\pi \cdot D_{d-D}^2}{\theta_{min,d}^2} = \frac{2\pi \cdot m_d \cdot e^4}{\hbar^2} \cdot \frac{2\lambda_{TF}^2}{E_d} = 3.45 \text{ Gbn} \quad (52)$$

[0162] The relative probability $P_{sc}(\pi/2 \leq \theta \leq \pi)$ to scatter in the back hemisphere ($\pi/2 \leq \theta \leq \pi$) is equal to:

$$P_{sc}(\pi/2 \leq \theta \leq \pi) = \frac{1}{\sigma_{d-D}} \cdot \int_{\pi/2}^{\pi} \left. \frac{d\sigma}{d\Omega} \right|_{d-D} \cdot 2\pi \cdot \sin \theta d\theta \quad (53)$$

[0163] For a deuteron projectile with $E_d = 3 \text{ MeV}$ and a deuteron target nucleus ($m_N = m_d$), the numerical value of $P_{sc}(\pi/2 \leq \theta \leq \pi)$ for screening by shell electrons ($\lambda_{sc} = \lambda_{TF} = 1.4a_0 = 7.4 \times 10^{-9} \text{ cm}$) is equal to:

$$P_{sc}(\pi/2 \leq \theta \leq \pi) = 1.57 \times 10^{-10} \quad (54)$$

[0164] and for screening by conduction electrons ($\lambda_{sc} = \lambda_{De,c} = 5 \times 10^{-10} \text{ cm}$) is equal to:

$$P_{sc}(\pi/2 \leq \theta \leq \pi) = 3.45 \times 10^{-8} \quad (55)$$

[0165] In the case of conduction electron screening in Eq. (55), the screened Coulomb potential energy $V_{C,sc}(r)$ is defined by the same as in Eq. (32) with $\lambda_{TF} \rightarrow \lambda_{sc} = \lambda_{De,c} = 5 \times 10^{-10} \text{ cm}$.

[0166] For a deuteron projectile with $E_d = 10 \text{ keV}$ and a deuteron target nucleus ($m_N = m_d$), the numerical value of the probability $P_{sc}(\pi/2 \leq \theta \leq \pi)$ for screening by shell electrons ($\lambda_{sc} = \lambda_{TF} = 1.4a_0 = 7.4 \times 10^{-9} \text{ cm}$) is equal to:

$$P_{sc}(\pi/2 \leq \theta \leq \pi) = 4.73 \times 10^{-8} \quad (56)$$

[0167] and for screening by conduction electrons ($\lambda_{sc} = \lambda_{De,c} = 5 \times 10^{-10} \text{ cm}$) is equal to:

$$P_{sc}(\pi/2 \leq \theta \leq \pi) = 1.04 \times 10^{-5} \quad (57)$$

[0168] Generally, the deep electron screening of Coulomb barrier (with $\lambda_{De,c} \ll \lambda_{TF}$) could significantly reduce the small angle elastic scattering dominance, increasing the probability of large angle scattering and correspondingly, increasing the astrophysical factor $S(E)$, and successful nuclear fusion events.

[0169] For an alpha (α) projectile with $E_\alpha = 3$ MeV and a deuteron target nucleus ($m_N = m_d$), the numerical value for $\sigma_{\alpha-D}$ (scattering) is as follows:

$$\sigma_{\alpha-D} = \int \left. \frac{d\sigma}{d\Omega} \right|_{\alpha-D} d\Omega \approx \frac{\pi \cdot D_{\alpha-D}^2}{\theta_{min,\alpha}^2} = \frac{8\pi \cdot m_\alpha \cdot e^4}{\hbar^2} \cdot \frac{a_{TF}^2}{E_\alpha} = 91.48 \text{ Mbn} \quad (58)$$

[0170] For an alpha (α) projectile with $E_\alpha = 1$ MeV and a deuteron target nucleus ($m_N = m_d$), the numerical value for $\sigma_{\alpha-D}$ (scattering) is as follows:

$$\sigma_{\alpha-D} = \int \left. \frac{d\sigma}{d\Omega} \right|_{\alpha-D} d\Omega \approx \frac{\pi \cdot D_{\alpha-D}^2}{\theta_{min,\alpha}^2} = \frac{8\pi \cdot m_\alpha \cdot e^4}{\hbar^2} \cdot \frac{a_{TF}^2}{E_\alpha} = 274.5 \text{ Mbn} \quad (59)$$

[0171] The target nucleus recoil energy could be found from the conservation of the total momentum in the elastic projectile particle-target nucleus scattering process:

$$\vec{p}_N = \vec{p}_p - \vec{p}'_p \quad (60)$$

[0172] Where \vec{p}_N is the target nucleus recoil momentum, \vec{p}_p is the momentum of the incident projectile particle, and \vec{p}'_p is the momentum of the scattered projectile particle. Since in elastic scattering $p_p = |\vec{p}_p| \approx |\vec{p}'_p|$ (for the reason that small angle scattering is the most probable event by a substantial margin), it follows from Eq. (60) that:

$$p_N^2 = \vec{p}_N^2 = \vec{p}_p^2 + \vec{p}'_p^2 - (2\vec{p}_p \cdot \vec{p}'_p \cdot \cos \theta) \approx 2p_p^2 \cdot (1 - \cos \theta) \quad (61)$$

[0173] where θ is the scattering angle. Correspondingly, the target nucleus recoil energy $E_N(\theta)$ follows from Eq. (61):

$$E_N(\theta) = \frac{p_N^2}{2m_N} \approx \frac{p_p^2}{m_N} \cdot (1 - \cos \theta) = \frac{2m_p}{m_N} \cdot E_p \cdot (1 - \cos \theta) \quad (62)$$

[0174] where $E_p = p_p^2/2m_p$ is the kinetic energy of the projectile particle.

[0175] The mean target nucleus recoil energy \bar{E}_N in a single elastic nonrelativistic projectile-target nucleus collision is obtained by averaging of $E_N(\theta)$ over $d\Omega$, and it follows from Eq. (60) with the usual substitution $\alpha \rightarrow \alpha_p = \theta_{min,p}^2/2$ that:

$$\bar{E}_N(\beta_p \ll 1) = \frac{\hbar^2}{m_N \cdot \lambda_{TF}^2} \cdot \ln\left(\frac{2}{\theta_{min,p}}\right) = \frac{\hbar^2}{m_N \cdot \lambda_{TF}^2} \ln\left(\frac{2\lambda_{TF}}{\hbar} \cdot \sqrt{2m_p \cdot E_p}\right) \quad (63)$$

[0176] since $\theta_{min,p} = \hbar/(\lambda_{TF} \cdot p_p) = \hbar/(\lambda_{TF} \cdot \sqrt{2m_p \cdot E_p}) \ll 1$.

[0177] For a proton projectile with $E_p = 3$ MeV and deuteron target nucleus ($m_N = m_d$), the numerical value for $\bar{E}_D(\beta_p \ll 1)$ is:

$$\bar{E}_D(\beta_p \rightarrow 1) = 41.4 \text{ meV} \quad (64)$$

[0178] For a deuteron projectile with $E_d = 3$ MeV and deuteron target nucleus ($m_N = m_d$), the numerical value for $\bar{E}_D(\beta_d \ll 1)$ is:

$$\bar{E}_D(\beta_d \rightarrow 1) = 42.7 \text{ meV} \quad (65)$$

[0179] For a deuteron projectile with $E_d = 10$ keV and deuteron target nucleus ($m_N = m_d$), the numerical value for $\bar{E}_D(\beta_d \ll 1)$ is:

$$\bar{E}_D(\beta_d \rightarrow 1) = 31.9 \text{ meV} \quad (66)$$

[0180] For an alpha (α) projectile with $E_\alpha = 3$ MeV and a deuteron target nucleus ($m_N = m_d$), the numerical value for $\bar{E}_D(\beta_\alpha \ll 1)$ is:

$$\bar{E}_D(\beta_\alpha \rightarrow 1) = 44.0 \text{ meV} \quad (67)$$

[0181] For an alpha (α) projectile with $E_\alpha = 1$ MeV and a deuteron target nucleus ($m_N = m_d$), the numerical value for $\bar{E}_D(\beta_\alpha \ll 1)$ is:

$$\bar{E}_D(\beta_\alpha \rightarrow 1) = 41.9 \text{ meV} \quad (68)$$

[0182] Thus, it can be concluded that the kinetic energy transfer to fuel nuclei (D) by either energetic light charged particles (e^- , e^+) or by energetic heavy charged particles (p , d , α) is very inefficient unless there is a mechanism to increase the probability of large angle scattering, for example, via increased density.

[0183] C. COMPTON SCATTERING OF PHOTONS ON TARGET NUCLEI

[0184] 1. COMPTON SCATTERING CROSS-SECTION

[0185] The differential Klein-Nishina cross section $d\sigma_C^{KN}/d\Omega$ per unit solid angle $d\Omega$ for Compton scattering of an electron on a deuteron is given by standard expression:

$$\frac{d\sigma_C^{KN}}{d\Omega} = \frac{r_D^2}{2} \left(\frac{1 + \cos^2 \theta}{(1 + \varepsilon_D(1 - \cos \theta))^2} + \frac{\varepsilon_D^2(1 - \cos \theta)^2}{(1 + \varepsilon_D(1 - \cos \theta))^3} \right) \quad (69)$$

[0186] where r_D is the deuteron classical radius $r_D = e^2/m_D c^2$, $\varepsilon_D = E_\gamma/m_D c^2$, and E_γ is the photon energy.

[0187] The total cross section σ_C^{KN} for a single scattering event is obtained by integrating the differential cross section for Compton scattering, given by Eq. (69), over $d\Omega$:

$$\sigma_C^{KN} = \int \frac{d\sigma_C^{KN}}{d\Omega} d\Omega = \int_0^\pi \frac{d\sigma_C^{KN}}{d\Omega} \cdot 2\pi \cdot \sin \theta d\theta \quad (70)$$

[0188] The above integration produces the standard known formula:

$$\sigma_C^{KN} = 2\pi r_D^2 \left(\frac{1 + \varepsilon_D}{\varepsilon_D^2} \left(\frac{2(1 + \varepsilon_D)}{1 + 2\varepsilon_D} - \frac{\ln(1 + 2\varepsilon_D)}{\varepsilon_D} \right) + \frac{\ln(1 + 2\varepsilon_D)}{\varepsilon_D} - \frac{1 + 3\varepsilon_D}{(1 + 2\varepsilon_D)^2} \right) \quad (71)$$

[0189] For $E_\gamma = 2$ MeV and ($m_N = m_d$), the numerical value for σ_C^{KN} is as follows:

$$\sigma_C^{KN} = 49.43 \text{ nbn} \quad (72)$$

[0190] For small $\varepsilon_D = E_\gamma/m_D c^2$, the expression σ_C^{KN} is reduced to:

$$\sigma_C^{KN}(\varepsilon_D \ll 1) = \frac{8\pi r_D^2}{3} \left(1 - 2\varepsilon_D + \frac{26}{5}\varepsilon_D^2 - \frac{133}{10}\varepsilon_D^3 + \frac{1144}{35}\varepsilon_D^4 \dots \right) \quad (73)$$

[0191] For $E_\gamma = 2 \text{ MeV}$ and $(m_N = m_d)$, the numerical value for $\sigma_C^{KN}(\varepsilon_D \rightarrow 1)$, calculated with the help of Eq. (73), is almost as in Eq. (72), namely:

$$\sigma_C^{KN}(\varepsilon_D \rightarrow 1) = 49.43 \text{ nbn} \quad (74)$$

[0192] 2. DEUTERON RECOIL ENERGY

[0193] The deuteron recoil energy $E_D(\theta)$, which is the kinetic energy transferred to a free (unbounded) deuteron by (γ -quanta) with energy E_γ , is given by the standard known expression:

$$E_D(\theta) = E_\gamma \cdot \varepsilon_D \cdot \frac{(1 - \cos \theta)}{1 + \varepsilon_D(1 - \cos \theta)}, \quad \varepsilon_D = \frac{E_\gamma}{m_D c^2} \quad (75)$$

[0194] where θ is the photon scattering angle. When $E_\gamma \ll m_D c^2$ (i.e., $\varepsilon_D \rightarrow 1$), then Eq. (75) is reduced to:

$$E_D(\theta) \approx \frac{E_\gamma^2}{m_D c^2} (1 - \cos \theta) = E_\gamma \cdot \varepsilon_D \cdot (1 - \cos \theta), \quad \varepsilon_D = \frac{E_\gamma}{m_D c^2} \ll 1 \quad (76)$$

[0195] Mean deuteron recoil energy \bar{E}_D in a single Compton collision is obtained by averaging of $E_D(\theta)$ from Eq. (75) with $d\sigma_C/d\Omega$ from Eq. (69) over $d\Omega$:

$$\bar{E}_D = \frac{\int E_D(\theta) \frac{d\sigma_C^{KN}}{d\Omega} d\Omega}{\frac{d\sigma_C^{KN}}{d\Omega}} = \frac{1}{\sigma_C^{KN}} \cdot \int_0^\pi E_D(\theta) \cdot \frac{d\sigma_C^{KN}}{d\Omega} \cdot 2\pi \cdot \sin \theta d\theta \quad (77)$$

[0196] The above integration produces the standard known expression:

$$\begin{aligned}
\bar{E}_D = E_\gamma \cdot (2\varepsilon_D(9 + 51\varepsilon_D + 93\varepsilon_D^2 + 51\varepsilon_D^3 - 10\varepsilon_D^4) \\
- 3(3 - \varepsilon_D)(1 + \varepsilon_D)(1 + 2\varepsilon_D)^3 \ln(1 + 2\varepsilon_D)) \\
\div (6\varepsilon_D(1 + 2\varepsilon_D)(2 + \varepsilon_D(1 + \varepsilon_D)(8 + \varepsilon_D)) \\
- 3(1 + 2\varepsilon_D)^3(2 + \varepsilon_D(2 - \varepsilon_D)) \ln(1 + 2\varepsilon_D)) \quad (78)
\end{aligned}$$

[0197] When $\varepsilon_D \rightarrow 1$ (i.e., $E_\gamma \ll m_D c^2$), then Eq. (78) is reduced to:

$$E_D(\varepsilon_D \rightarrow 1) = E_\gamma \cdot \varepsilon_D \cdot \left(1 - \frac{11}{5}\varepsilon_D + \frac{51}{10}\varepsilon_D^2 - \frac{3931}{350}\varepsilon_D^3 \dots\right) \quad (79)$$

[0198] For $E_\gamma = 2$ MeV and ($m_N = m_d$), the numerical value for $\bar{E}_D(\varepsilon_D \rightarrow 1)$ is as follows:

$$\bar{E}_D(\varepsilon_D \rightarrow 1) = 2.13 \text{ keV} \quad (80)$$

[0199] In the case of Compton scattering on free electrons, when $E_\gamma = 2$ MeV, then $\varepsilon_e = E_\gamma/m_e c^2 = 3.914$. It thus follows from Eq. (78) that in the case ($r_D \rightarrow r_e$), $\bar{E}_e = 1.062$ MeV. For $E_\gamma, E_\gamma = 1.022$ MeV, $\varepsilon_D = E_\gamma/m_e c^2 = 2$, and it follows from Eq. (78) that $\bar{E}_e = 0.453$ MeV.

[0200] Therefore, the kinetic energy transfer to fuel nuclei (D) by energetic photons is much more efficient than by energetic light charged particles (e^-, e^+), or by energetic heavy charged particles (p, d, α).

[0201] D. NEUTRON SCATTERING NUCLEI

[0202] 1. NEUTRON ELASTIC SCATTERING ON DEUTERON NUCLEI

[0203] Since the deuteron nucleus possesses just a single (ground) energy level, the neutron scattering on the deuteron is an elastic scattering process if energy the neutron is below the disintegration of the deuteron by the neutron (where the deuteron disintegration

threshold by a neutron is $K_n^{th} = 3.4$ MeV). In this case, it is known that the neutron elastic cross section $\sigma_{sc}(\theta_{CM})$ is isotropic in CM (the center of mass frame), that is,

$$\sigma_{sc}(\theta_{CM}) = \frac{\sigma_{sc}}{4\pi} \quad (81)$$

[0204] where θ_{CM} is the neutron scattered angle in CM and σ_{sc} is the total neutron elastic cross section. The scattering angle θ_{lab} in lab frame is related to θ_{CM} as:

$$\tan \theta_{lab} = \frac{m_d \cdot \sin \theta_{CM}}{m_n + m_d \cdot \cos \theta_{CM}} \quad (82)$$

[0205] where m_n and m_d are the neutron and deuteron masses, respectively.

[0206] Since the scattered angles θ_{CM} and θ_{lab} are different, the angular distributions of scattered particles in CM and lab are also different. However, the number of scattered particles in the corresponding solid angle $d\Omega(\theta_{CM})$ in CM and in solid angle $d\Omega(\theta_{lab})$ in lab must be the same:

$$\sigma_{sc}(\theta_{lab})d\Omega(\theta_{lab}) = \sigma_{sc}(\theta_{CM})d\Omega(\theta_{CM}) \quad (83)$$

[0207] However, $d\Omega(\theta_{CM}) = 2\pi \sin \theta_{CM} d\theta_{CM}$ and $d\Omega(\theta_{lab}) = 2\pi \sin(\theta_{lab}) d\theta_{lab}$.

Therefore, Eq. (83) becomes:

$$\sigma_{sc}(\theta_{lab}) \sin(\theta_{lab}) d\theta_{lab} = \sigma_{sc}(\theta_{CM}) \sin(\theta_{CM}) d\theta_{CM} \quad (84)$$

[0208] With the help of Eq. (82), it follows from Eq. (84) that the angular distribution of scattered particles in lab could be determined from the corresponding angular distribution of scattered particles in CM as follows:

$$\sigma_{sc}(\theta_{lab}) = \sigma_{sc}(\theta_{CM}) \cdot \frac{(m_n^2 + m_d^2 + 2m_n \cdot m_d \cdot \cos(\theta_{CM}))^{3/2}}{m_d^2 \cdot (m_d + m_n \cdot \cos(\theta_{CM}))} \quad (85)$$

[0209] The relation between scattered neutron velocities, $\vec{v}'_{n,CM}$, in CM and $\vec{v}'_{n,lab}$ in lab, is given by the formula:

$$\vec{v}'_{n,lab} = \vec{v}'_{n,CM} + \vec{v}_{CM}, \vec{v}_{CM} = \frac{m_n}{m_n + m_d} \vec{v}_n \quad (86)$$

[0210] where \vec{v}_{CM} is the center mass velocity and \vec{v}_n is the neutron velocity in lab.

Correspondingly, the relation between neutron and deuteron velocities $\vec{v}_{n,CM}$, $\vec{v}_{d,CM}$ in CM and \vec{v}_n , \vec{v}_d in lab are as follows:

$$\vec{v}_{n,CM} = \vec{v}_n - \vec{V}_{CM} = \frac{m_d}{m_n + m_d} \vec{v}_n, \vec{v}_d = 0, \vec{v}_{d,CM} = -\vec{V}_{CM} = -\frac{m_n}{m_n + m_d} \vec{v}_n \quad (87)$$

[0211] Since the magnitude of neutron velocity in CM does not change after collision (i.e., $\vec{v}'_{n,CM} = \vec{v}_{n,CM}$), it follows with the help of Eq. (86) and Eq. (87) that:

$$\begin{aligned} v_{n,lab}^2 &= v_{n,CM}^2 + V_{CM}^2 + 2v_{n,CM}V_{CM} \cos \theta_{CM} \\ &= \frac{(m_n^2 + m_d^2 + 2m_n m_d \cos \theta_{CM})}{(m_n + m_d)^2} v_n^2 \end{aligned} \quad (88)$$

[0212] Rewriting Eq. (88) in terms of the neutron kinetic energy K'_n after the collision and the neutron kinetic energy K_n before the collision yields:

$$K'_n = \frac{(m_n^2 + m_d^2 + 2m_n m_d \cos \theta_{CM})}{(m_n + m_d)^2} K_n \quad (89)$$

[0213] It is convenient to introduce the new parameter α_n by the following definition:

$$\alpha_n = \frac{(m_d - m_n)^2}{(m_d + m_n)^2} \quad (90)$$

[0214] Then, in term of the new parameter α_n , Eq. (89) is reduced to:

$$K'_n = \frac{1}{2} K_n \cdot \left((1 + \alpha_n) + ((1 - \alpha_n) \cdot \cos \theta_{CM}) \right) \quad (91)$$

[0215] From Eq. (91), the kinetic energy K'_n is in the following limits ($0 < \theta_{CM} < \pi$):

$$\alpha_n \cdot K_n \leq K'_n \leq K_n \quad (92)$$

[0216] The probability distribution $P(K_n \rightarrow K'_n) \cdot dK'_n$ is, by definition, the probability that the neutron with initial kinetic energy K_n will acquire kinetic energy in the energy gap $(K'_n, K'_n + dK'_n)$ after the collision. The probability that the neutron will be scattered in the interval $(\theta_{CM}, \theta_{CM} + d\theta_{CM})$ is given by:

$$\frac{\sigma_{sc}(\theta_{CM}) \cdot d\Omega(\theta_{CM})}{\sigma_{sc}} = \frac{\sigma_{sc}(\theta_{CM}) \cdot 2\pi \sin(\theta_{CM}) d\theta_{CM}}{\sigma_{sc}} \quad (93)$$

[0217] where $\sigma_{sc}(\theta_{CM})$ is the neutron differential elastic cross section and σ_{sc} is the total neutron elastic cross section in CM. It is apparent that they are the same probabilities:

$$P(K_n \rightarrow K'_n) \cdot dK'_n = -\frac{\sigma_{sc}(\theta_{CM}) \cdot 2\pi \sin(\theta_{CM})}{\sigma_{sc}} \cdot d\theta_{CM} \quad (94)$$

[0218] since for $d\theta_{CM} > 0 \rightarrow dK'_n > 0$, thus providing the positivity of the probability $P(K_n \rightarrow K'_n) > 0$.

[0219] From Eq. (91), it follows that:

$$dK'_n = -\frac{1}{2}K_n \cdot (1 - \alpha_n) \cdot \sin \theta_{CM} d\theta_{CM} \quad (95)$$

[0220] Substitution of Eq. (95) into Eq. (94) yields:

$$P(K_n \rightarrow K'_n) = \frac{4\pi \cdot \sigma_{sc}(\theta_{CM})}{K_n \cdot (1 - \alpha_n) \cdot \sigma_{sc}} \text{ for } (\alpha_n \cdot K_n \leq K'_n \leq K_n) \quad (96)$$

[0221] Since the neutron elastic cross section $\sigma_{sc}(\theta_{CM})$ is isotropic in CM, then substitution of $\sigma_{sc}(\theta_{CM}) = \sigma_{sc}/4\pi$ from Eq. (81) into Eq. (96) yields:

$$P(K_n \rightarrow K'_n) = \frac{1}{K_n \cdot (1 - \alpha_n)} \text{ for } (\alpha_n \cdot K_n \leq K'_n \leq K_n) \quad (97)$$

[0222] Therefore, the kinetic energy probability distribution $P(K_{n1} \rightarrow K'_n)$ is independent on K' in the whole interval.

[0223] 2. NEUTRON ENERGY LOSS IN ELASTIC COLLISIONS WITH DEUTERON NUCLEI

[0224] By definition, the average neutron energy \bar{K}'_n after elastic collision is obtained by averaging the kinetic energy with the probability distribution, $P(K_n \rightarrow K'_n)$ given by Eq. (97):

$$\bar{K}'_n = \frac{\int_{\alpha K_n}^{K_n} K'_n \cdot P(K_n \rightarrow K'_n) dK'_n}{\int_{\alpha K_n}^{K_n} P(K_n \rightarrow K'_n) dK'_n} = \frac{1}{2} \cdot K_n \cdot (1 - \alpha_n) \quad (98)$$

[0225] The average kinetic energy \bar{K}'_d transferred to the deuteron nucleus in an elastic collision of a neutron on a deuteron is equal to $K_n - \bar{K}'_n$ (see also Eq. (90)):

$$\bar{K}'_d = K_n - \bar{K}'_n = \frac{1}{2} \cdot (1 - \alpha_n) \cdot K_n = \frac{2m_n \cdot m_d}{(m_n + m_d)^2} \cdot K_n = \frac{4}{9} \cdot K_n \quad (99)$$

[0226] which is equal to one half of the maximum energy transfer in a head-on collision:

$$K'_{d,max} = \frac{4m_n m_d}{(m_n + m_d)^2} \cdot K_n \quad (100)$$

[0227] for a neutron projectile on a deuteron target nucleus, with the total elastic cross section of the order of:

$$\sigma_{sc} = 3 \text{ bn} \quad (25 \text{ meV} \leq K_n \leq 2 \text{ MeV}) \quad (101)$$

[0228] THEORETICAL SUMMARY

[0229] Electron screening plays a critical role in the overall efficiency of nuclear fusion events between charged particles. The kinetic energy transfer to fuel nuclei (D) by neutral particles, such as energetic neutrons or photons, is shown above to be far more efficient than by energetic charged particles, such as light particles (e^- , e^+) or heavy particles (p , d , α).

[0230] A theoretical framework is also provided for D-D nuclear fusion reactions in high-density cold fuel nuclei embedded in metal lattices, with a small fraction of fuel activated by hot neutrons. The important role of electron screening is also established in increasing the relative probability $P_{sc}(\pi/2 \leq \theta \leq \pi)$ to scatter in the back hemisphere ($\pi/2 \leq \theta \leq \pi$), an essential requirement for subsequent tunneling of reacting nuclei to occur. The applicability of the concept of electron screening potential energy U_e to the calculation of the nuclear cross section enhancement factor $f(E)$ is also clarified. The expression for U_e for the general electron screening process is also derived, using the unifying concept of screening length λ_{sc} .

[0231] EXPERIMENTAL SETUP AND RESULTS

[0232] Based on the results of the theoretical analysis below, a highly screened environment in deuterated metals was selected. Such an environment features the fuel in a very high-density state, together with efficient screening by both shell and conduction electrons, or external ionization or Compton electrons from photon irradiation. Local fusion events were then initiated using hot neutrons that originate from photodisintegration of deuterons bombarded by photons above the 2.226 MeV level. The hot neutrons scatter and efficiently deliver nearly half of their energy to a relatively cold deuteron. The hot deuteron is then able to be scattered at a large angle with a nearby cold deuteron in a highly screened environment, leading to efficient nuclear tunneling and fusion.

[0233] This process is fundamentally different than other fusion processes in which all of the fuel nuclei are hot and reside in a weakly screened environment (e.g., in a Tokamak). Such an environment would be dominated by small angle nonproductive

elastic Coulomb scattering with an inefficient tunneling probability. Maintaining one of the two fusing nuclei in a relatively cold and well-screened condition provides highly efficient large angle scattering and subsequent tunneling probabilities. Secondary processes following the initial fusion event include kinetically heated boosted fusion reactions, conventional secondary channels with ^3He , ^3H , alpha particles, etc., and potentially highly energetic interactions with the metal lattice nuclei, including Oppenheimer-Phillips stripping reactions. The goal in this experimentation was to explore fusion processes that make optimal use of highly electron screened environments with high density fuel in a manner conducive to process multiplication via effective secondary reactions. The experiments described herein were guided by the theoretical analysis below, as well as the novel reactions previously observed by the inventors using Bremsstrahlung radiation.

[0234] D-D nuclear fusion events were observed in an electron-screened, deuterated metal lattice by reacting relatively cold deuterons with relatively hot deuterons (d^*) produced by elastically scattered neutrons originating from Bremsstrahlung photodissociation. Exposure of deuterated materials (e.g., ErD_3 and TiD_2) to photon energies in the range of 2.5 to 2.9 MeV resulted in photodissociation neutrons below 400 keV and 2.45 MeV neutrons consistent with $\text{D}(d,n)^3\text{He}$ fusion. Additionally, neutron energies of approximately 4 and 5 MeV for TiD_2 and ErD_3 were measured, consistent with either “boosted” neutrons from kinetically heated deuterons or other capture processes.

[0235] Neutron spectroscopy was conducted using calibrated lead-shielded liquid (EJ309) and plastic (Stilbene) scintillator detectors. The data supports the subsequent

theoretical analysis, predicting fusion reactions and subsequent reactions in highly screened environments. Such screening is naturally provided by shell and metal lattice electrons and by Compton scattering of the Bremsstrahlung radiation, providing plasma channels and further enhancing screening.

[0236] A. ELECTRON ACCELERATOR AND GENERAL LAYOUT

[0237] Tests were performed using a Dynamitron electron accelerator having independent control of beam energy (450 keV to 3.0 MeV) and beam current (10 μ A to 30 mA), as shown in experimental reactor 700 of FIG. 7A. The cave 710 is shown more clearly in FIG. 7B. The radiofrequency-accelerated electron beam enters the beam room via an evacuated tube and is scanned over the braking target, utilizing the scanning magnet \sim 1 m above the target. The beam was operated in photon mode for the current tests, utilizing a 1.2 mm-thick tantalum braking target. Samples in glass vials were placed on an aluminum exposure tray close to the tantalum braking target and were exposed while the electron beam scanned at a frequency of 100 Hz over the length of 0.91 m. FIGS. 7A and 7B show the relative position of the 16 samples (total length 0.46 m) and lead cave 710, which housed the neutron detectors and is described below. FIG. 7C is a magnified view 720 of experimental reactor 700 illustrating the close proximity (11.2 mm distance) of the 20 ml sample vials relative to the braking target, which was cooled with ambient-temperature water flowing spanwise in a stainless-steel cooling channel. FIG. 8 shows a more general architecture 800 of the experimental setup, in which electrons are accelerated within a linear accelerator, impinging upon a high Z metal target from which Bremsstrahlung gamma radiation is emitted to impinge upon the sample, which includes a deuterated metal.

[0238] B. CAVE DESCRIPTION

[0239] Due to the intense gamma flux, the detectors (a), (b), (c) were placed in a thick lead cave 710 with the following dimensions: front wall – 30.5 cm (12 in); top and side walls – 15.3 cm (6 in); and base and rear walls – 10.1 cm (4 in). The distance from the sample centerline to the detectors was 0.76 m. Borated polyethylene (B-PE) was used to reduce the large flux of thermal neutrons entering from the sides of the cave to minimize the gamma signals from the reaction $\text{Pb}(n, \gamma)$ from the cave walls, thus improving signal quality. The B-PE thickness was 2.5 cm for the top, sides, and back and 2.5 cm B-PE plus 5 cm normal high-density standard PE for the base of cave 710.

[0240] C. BEAM CHARACTERISTICS

[0241] 1. PHOTON FLUX

[0242] The high Dynamitron beam current exposed the samples to intense photon flux. Figure 3 provides the photon spectrum for the peak electron beam energy of 2.9 MeV at the top of the sample, as determined using the fitted 5-term interpolation formula, 450 μA of current (per vial):

$$N_\gamma(E_\gamma) = (c_0 + c_1 \cdot E_\gamma) \cdot \left(\frac{E_\gamma}{E_\gamma^{\max}} \right)^{\alpha_0 + \alpha_1 \cdot E_\gamma} \cdot \left(1 - \frac{E_\gamma}{E_\gamma^{\max}} \right)^\beta \quad (102)$$

[0243] where E_γ^{\max} is the maximum photon energy per one incident electron and E_γ is photon energy in MeV, with $N_\gamma(E_\gamma)$ in units of photon/second/MeV/Steradian. The constants used were $c_0 = -3.187 \times 10^{-3}$, $c_1 = 3.506 \times 10^{-3}$, $\alpha_0 = -2.035$, $\alpha_1 = -3.189 \times 10^{-2}$, and $\beta = 6.327 \times 10^{-1}$.

[0244] 2. BEAM ENERGY MEASUREMENT

[0245] Beam energy was monitored by measuring a current through a linear stack of resistors to measure the terminal voltage on the electron accelerator. The beam voltage was recorded using a Labview Data Acquisition system and a high-speed triggering scope for short-term transients. The Dynamitron was very stable in beam energy (e.g., $2.9 \text{ MeV} \pm 100 \text{ keV} (5\sigma)$). Current was also measured and was stable to within 2.5% (5σ) of setpoint. During pre-test evaluation of the Dynamitron, the terminal voltage was checked by exposing beryllium near its photodissociation peaks of 1.76 and 2.42 MeV. By examining the change in the first and second derivatives of neutron production rates, it was determined that the photon beam energy was less than 50 keV of the specified set point, agreeing with the beam terminal voltage measurement method, which was used for all subsequent tests.

[0246] 3. PHOTODISSOCIATION NEUTRONS

[0247] With the beam operating above the deuteron photodissociation energy (2.226 MeV), photo-neutrons were produced. The peak and average photodissociation neutron energies were calculated, as shown in Table II below.

TABLE II: CALCULATED PHOTODISSOCIATION NEUTRON ENERGIES

Beam Energy ($h\nu$)	Neutron Energy (MeV)		
	Nominal Energy	Aligned with Beam (0° Direction)	Counter to Beam (180° Direction)
2.5	0.135	0.144	0.127
2.7	0.235	0.246	0.224
2.9	0.335	0.348	0.321
3.0	0.385	0.399	0.370

[0248] D. NEUTRON DETECTION

[0249] 1. PROMPT NEUTRON DETECTION

[0250] Three different neutron detection systems were employed, as noted in Tables III(A) and III(B) below.

TABLE III(A): NEUTRON DETECTION INSTRUMENT DETAILS

Detector:	Neutron Detection Technology (Manufacturer):	Detector Material:	Detector Dimensions (cm):	Location (Distance from Specimens as Noted):
Eljen-309 (HV)	Liquid scintillator; proton recoil (Eljen)	Xylene-based liquid	5 cm diam. by 10 cm length	In cave (0.76 m)
Stilbene (St1)	Plastic, single crystal; proton recoil (InRad Optics)	Stilbene crystals wrapped in PTFE tape; optically polished on face + fused silica window	2.5 cm diam. by 2.5 cm length	In cave (0.76 m)
LaBr ₃	Lanthanum bromide detector	LaBr ₃ crystal	3.8 cm diam. by 3.8 cm length	In the rear of the cave, rotated 90° and offset toward the entry door

TABLE III(B): NEUTRON DETECTION INSTRUMENT DETAILS

Detector:	PMT Voltage (V):	Detector Efficiency (Average):	Energy Detection:
Eljen-309 (HV)	-1100	11%	Neutron: 0.5 to 15 MeV
Stilbene (St1)	730	13%	Neutron: 0.3 to 15 MeV
LaBr ₃	730	Gamma: ~15% < 1 MeV ~5% 1 to 4.4 MeV 0.1% > 4.4 MeV	0 to 10 MeV

[0251] The Eljen-309 liquid scintillator and the Stilbene single-crystal detector were used to detect prompt fast neutron counts and energies. The Eljen detector (5 cm diameter by 10 cm length) being larger than the Stilbene detector (2.5 cm diameter by 2.5 cm length), had a higher sensitivity to the fast neutrons, resulting in a greater signal. However, due to the unique single-crystal material, the Stilbene could measure slightly

lower energy neutrons (0.3 MeV threshold) versus the EJ309 (0.5 MeV threshold). Both detectors pointed toward the specimens during radiation and were shielded from the intense gamma rays with the 30.5 cm front lead wall and surrounding cave. It was found that the Stilbene detector exhibited greater photon/neutron discrimination due to its material and design. A lanthanum bromide (LaBr_3) gamma detector was also placed in the cave (near the rear) and was used to measure gamma energies from both the beam and from thermal neutron capture on the lead walls, resulting in $\text{Pb}(n, \gamma)$ reactions.

[0252] A rough estimate of photo-neutrons interacting with the cave was determined by counting the 3 to 8 MeV gammas created during beam on conditions. It is previously noted that to reduce the gamma glow within the cave to acceptable levels, borated polyethylene was placed on all five sides of the cave (except the front), thus minimizing the captured thermal neutrons to reduce the ionizing radiation from the $\text{Pb}(n, \gamma)$. By using the B-PE around the cave, higher beam currents could be utilized, increasing the process signal-to-background noise for the fueled shots to meet the goal of accurately measuring fusion and other reaction neutrons.

[0253] 2. PROMPT NEUTRON SIGNAL POSTPROCESSING

[0254] High-intensity primary Bremsstrahlung and secondary fluorescence x-rays from the Dynamitron beam were the most significant challenges for postprocessing the detector signal, even though the detectors were shielded in the lead cave. The strategy was to record all detector signals without any information loss with the fast data acquisition system (DAQ) throughout the beam exposure. A sophisticated model-based pulse-shaped discrimination (PSD) signal analysis procedure was developed for the postprocessing data analysis.

[0255] The detector photomultiplier tube (PMT) signal output was directly connected to a CAEN, 8-channel DT5730 desktop digitizer with 500-MHz sampling rate and 14-bit resolution, which is well suited for the signal from the organic scintillators. The pulse-processing-(DPP)-PSD firmware and control software, CoMPASS, of the digitizer were used for the on-line signal processing, data acquisition monitoring, and waveform recording. Each detector signal was triggered locally at the input channel and recorded independently with the DPP firmware. The Universal Serial Bus (USB) 2.0 interface of the digitizer allows data transfer at a speed of up to 30 MB/s. During the experiment, the data transfer speed was monitored, and data overflow was prevented by increasing the detection threshold, reducing the beam current, reducing the number of detector channels, or increasing the shielding materials. A total of 140 samples (280 ns long) of each signal waveform were recorded for the postprocessing.

[0256] 3. ENERGY CALIBRATION

[0257] The energy scales of the pulse height spectrum of the detector were periodically calibrated using Cs-137, Co-60, and Th-232 check sources. The PMT gains and calibration stability were important for the PSD performance, the neutron spectrum unfolding, and combining and/or comparing separate sets of experimental data. The detector gain stability across the measurements was confirmed (and corrected) using the 511 keV line during off-line analysis. The neutron detection efficiency of the detector was determined from the known spectra of the AmBe and Cf-252 sources. Average detector efficiency was calculated to be approximately 13% for the Stilbene detectors and 11% for the EJ-309 detectors. Energy-dependent efficiency was used for the

response matrix normalization and subsequently for the neutron flux calculation of the detector unfolding.

[0258] 4. HYBRID PSD APPROACH

[0259] A hybrid PSD technique was used to minimize false neutron counting. The most important filter to remove double peaks and false neutron counting is the Pile-Up signal rejection (PUR). If small peaks (spikes) with amplitudes exceeding 8% of the main peak were observed on the tail of the signal, the signal was rejected from further processing. The rejection criterion was set to 5% for the stronger signals above 1 MeV. The PUR criteria cannot be tighter because the delayed secondary scintillator phosphorescence light pulses from the scintillation process itself gives the PSD information. Smaller x-ray signals (spikes) could pass through the pile-up rejection criteria. Also, successive neutron recoils within the phosphorescence decay will alter PSD performance. These types of events were further reduced by the signal root-mean-square (RMS) and baseline shift filters.

[0260] The pile-up rate increases with the beam energy and current. For example, at beam conditions of 2.9 MeV and 15 mA the filters rejected about 35% of all triggered signals. All signals that passed through those filters were subsequently plotted in the PSD spectrum. The neutron pulse height spectrum was accepted if the PSD parameter was above an 8σ threshold of the gamma ray band. Therefore, “accepted” waveform shapes reliably resulted in neutron signatures. The PUR algorithm coupled with the 8σ constraint on the PSD between neutron and gamma PSD parameter virtually eliminated neutron double hits (aliasing) and gamma signals being recorded as neutrons. The 8σ constraint also reduced fast-neutron counts considerably, but significantly increased the

fidelity of the overall data and the neutron energy measurement. For reference purposes, the peak photo neutrons produced were less than 400 keV. This was below the Eljen-309 threshold and was also below the Stilbene ability to measure on account of the 8σ constraint window used to ensure separation of neutrons from gammas in the PSD.

[0261] 5. NEUTRON ENERGY DETERMINATION

[0262] As discussed above, the detectors were calibrated in electron-equivalent units, as were the measured neutron pulse height spectra. The steps used to unfold the detector response include the following. First, MCNPX-Polimi and MPPost postprocessing codes were used to generate the detector response matrix. Subsequently, the HEPROW computer code package obtained from Oak Ridge National Lab (RSICC), which used Bayes theorem and maximum entropy methods, was utilized for the spectrum unfolding. Three different unfolding codes were evaluated: GRAVELW, UNFANAW, and MIEKEW. The final reported results used the UNFANAW code, which provided more consistent results with the known multipeak AmBe neutron spectrum unfolding.

[0263] The input files of the unfolding code were the experimental spectra and the detector response matrix. The response matrix is the ideal pulse height spectra with monoenergetic neutrons hitting the detector. Neutron count uncertainty is assumed to be the standard uncertainty assigned to contents in one channel assuming Poisson statistics hold, and is the square root of the number of counts. It is also assumed that no correlation exists between different channels. The neutron penetration through the cave (lead and B-PE) was simulated using the MCNP6 code. For reference purposes, the lead cave scattered approximately 80% of incoming fusion neutrons.

[0264] E. SAMPLE MATERIALS AND METHODOLOGY

[0265] 1. SAMPLE MATERIALS

[0266] The samples exposed in this study were created from prepared batches of either deuterated or bare (no-load) erbium or titanium metal material. Table IV below provides the materials, test shot identifier, shot durations, energy, and current settings that were used. In the test shot exposures, ErD_3 (480 g in 16 vials) and TiD_2 (216 g in plate and powder form) samples containing 5×10^{24} deuterium atoms were used. No additional deuterium atoms were added to the samples.

TABLE IV: TEST SHOT SAMPLE EXPOSURES

Test Shot ID	Material	Exposure Duration (min)	Beam	
			Energy (MeV)	Current (mA)
TS 589 (a,a2,f,g,Rd)	Er,bare	270	2.9	15
TS 589Ra	Er, bare	30	2.5	15
TS 589b2	Er, bare	30	2.7	15
TS 589c2	Er, bare	30	2.8	15
TS 589d2	Er, bare	30	3.0	15
TS 589Rb	Er, bare	30	2.9	5
TS 589Rc	Er, bare	30	2.9	10
TS 589Re	Er, bare	15	2.9	25
TS 589Rf	Er, bare	15	2.9	30
TS1575 (a,Ra,Rb)	ErD_3	360	2.9	15
TS1575Rb	ErD_3	30	2.9	5
TS1575Rc	ErD_3	30	2.9	10
TS1575Rd	ErD_3	30	2.9	20
TS1575Re	ErD_3	15	2.9	25
TS1575Rf	ErD_3	15	2.9	30
TS1576 (c,c2,e,Rb)	ErD_3	360	2.9	15
TS1576Ra	ErD_3	60	2.5	15
TS1576a	ErD_3	30	2.7	15
TS1576b	ErD_3	30	2.8	15
TS1576d	ErD_3	30	3.0	15
TS(610,611,611R,612)	TiD_2	330	2.9	15
TS631	Ti, bare	60	2.9	15

[0267] In Table IV, black rows indicate baseline configuration, gray rows indicate beam energy study, and white rows indicate beam current study. Note that test shots

TS1575 and 1576 were distinct samples made from ErD_3 and were exposed to evaluate reproducibility. These samples evaluated reproducibility of the process using specimens made from different material batches and exposed on different test days, and outcomes were comparable. Samples were tracked using meticulous records for custody control from material loading through exposure and posttest analysis using high-purity germanium (HPGE) gamma scans and liquid beta scintillator counting.

[0268] For each test, the samples were placed into glass vials and subsequently positioned at a close distance to the tantalum braking target (see FIG. 7C) to maximize the flux per unit area per unit time to evaluate the hypothesis that fusion events could be initiated with ionizing radiation in deuterated metal lattices where the deuterium fuel was in a stationary center-of-mass frame. Natural-abundance erbium (99% purity) and titanium (99% purity) were deuterated by gas loading using appropriate pressure, temperature, and time protocols. Erbium was chosen for this study for several reasons: (1) Erbium loads to ErD_3 have a high fuel number density (8×10^{22} D-atoms/cm³); (2) Erbium showed enhanced nuclear reactions via LINAC exposure in previous tests; (3) Erbium metal maintains a high deutron stoichiometry between furnace D-loading and testing; and (4) Erbium ($Z = 68$) provides a mid-range of metal lattice screening without excessive metal lattice interaction reducing fusion reactions.

[0269] Titanium was also exposed under comparable conditions to examine the effect of lower AMU ($Z = 22$), approximately 1/3 the positive nuclear charge of Er, which also contributed to fewer metal lattice screening electrons. The sample mass change (accuracy $\pm 5\%$) from before until after gas loading was used to determine the D-loading of the sample materials. Note 99.999% ultra-high-purity gas was used to

deuterate the samples. Although the vials were sealed during exposure, air was used as the cover gas.

[0270] 2. CASE-CONTROL METHODOLOGY

[0271] A case-control methodology was utilized, where identical tests were performed on fueled and unfueled samples, to isolate the fuel as the only experimental variable. For consistency between the ErD_3 and TiD_2 , the same amount of fuel (5×10^{24} D-atoms) was exposed. This amounted to 480 g of ErD_3 or 216 g TiD_2 , respectively, exposed in 16 vials. For the unfueled case, a comparable mass of bare Er and bare Ti was exposed. As will be shown in the results below, during unfueled shots, there was some neutron activity above cosmogenic background. This activity is believed to have been caused by screened reactions from the naturally occurring deuterium (153 ppm) in various standard water-cooling passages in the Dynamitron that were exposed to either direct or indirect gamma irradiation. For reference, the braking target cooling channel contained 1.6×10^{22} D-atoms and the scanner side cooling passages contained 1.2×10^{22} D-atoms.

[0272] III. EXPERIMENTAL RESULTS

[0273] A. PULSED SHAPE DISCRIMINATION SPECTRA

[0274] FIG. 10A provides an example Pulse Shape Discrimination (PSD) plot 1000 relating PSD parameters versus electron equivalent energy recorded in the detector (EJ309 HV) for TS1576 ErD_3 with beam conditions of 2.9 MeV and 15 mA and a 6-hour exposure. As noted in the Neutron Detection section, an 8σ constraint window was used to ensure separation of neutrons from gammas. Data points occurring above the 8σ separator line were confidently counted as neutrons and not gammas.

[0275] B. COMPARISON OF FUELED VERSUS UNFUELED RESULTS

[0276] As described above, a case-control methodology was followed where ErD_3 (fueled) samples and Er-bare (unfueled) samples were exposed in separate exposures, holding constant all other experimental parameters, including sample material type and mass, beam energy and current, sample placement under the beam, detector placement, and cave configuration. FIG. 10B is a graph 1010 that presents the EJ309 detector results for TS1576 (fueled, black line above) and TS589 (unfueled, dark gray line below) in detector counts (PMT counts after filtered using the process noted earlier) versus electron energy equivalent units (keVee). The small spikes to the right of the peaks are all from the fueled results. FIG. 10C is a graph presenting the net counts (TS1576 (fueled) minus TS589 (unfueled) prior to unfolding with the HEBROW algorithms. The 6-hour data shows significantly higher detector counts during the fueled exposures. It is noted that the shape of the curve for ErD_3 in the 0 to 1000 keVee range bears significant resemblance previous results by Lang, who used a similar scintillator/PSD approach to measure neutron energies for a 35-DD-W-S NSD/Gradel Fusion D-D fusion neutron generator.

[0277] C. NEUTRON SPECTRA AND REPRODUCIBILITY

[0278] Utilizing the methods for the detector modeling and neutron energy unfolding described earlier, the “net” (fueled minus unfueled) PSD data was converted into neutron spectra. Graphs 1100, 1110, 1120 of FIGS. 11A-C present data showing neutron spectra measured for the 6-hour aggregate data for two separate ErD_3 test samples. FIGS. 11A-C show evidence of (1) fusion neutron production (all); (2) neutrons with greater than fusion energies (EJ309); and (3) reproducibility of the process. The

uncertainty bars represent 3σ . Fusion energy neutron counts were scaled to sample location. TS1575 1.5×10^3 neutron counts per second and TS1576 1.6×10^3 neutron counts per second using EJ309 and 14×10^3 neutron counts per second using the Stilbene detector. It should be noted that the Stilbene detector exhibits better gamma/neutron separation, and thus, fewer true neutrons are discarded during postprocessing, resulting in the higher neutron count rate.

[0279] FIG. 11A is for TS1575 and FIG. 11B is for TS1576. Both were corrected for background/unfueled. The unfolded neutron spectra showed a number of interesting features, including several primary neutron energy peaks of 2.45, 4, and to a lesser degree, 5 MeV, plus an apparent shoulder peak 4.2 MeV. The measured neutron energies were remarkably close, indicating process reproducibility. FIG. 5C shows the neutron spectra for TS1575 measured using the solid-state Stilbene detector, showing the nominal 2.45-MeV fusion neutron peak, which was in the calibrated range of the detector. The higher energy peaks occur in the nonlinear range of the detector, and are not presented here.

[0280] D. ALTERNATE MATERIAL EXPOSURE: TITANIUM DEUTERIDE

[0281] Graph 1200 of FIG. 12 shows the neutron spectra for TiD_2 using the EJ309 detector for the “net” fueled (TS611-612) minus unfueled (TS631) PSD data. The unfolded neutron spectra showed a number of interesting features, including several primary neutron energy peaks of 2.45 (fusion energy), 4, and to a lesser degree 5 MeV, and an apparent shoulder peak 4.2 MeV. It is noted that the fluence fusion-energy neutron peak is approximately 20% higher for the TiD_2 than for the ErD_3 , accounting also for the exposure times.

[0282] E. MEASUREMENT UNCERTAINTY

[0283] The uncertainty bars for the neutron spectra in FIGS. 11A-C and 12 were determined based on the combined effect of detector energy resolution and the unfolding algorithm. The neutron energy uncertainty (horizontal band) was determined using the perturbation method. First the standard deviation in electron equivalent units was determined by examining the response of the detectors to established gamma peaks for standard check sources (Cs-137 and Co-60) by fitting a Gaussian distribution resulting in a $\sigma \sim 50$ keVee. To obtain the plotted 3σ , the original spectrum was “offset” by either +150 keVee or -150 keVee, corresponding to $\pm 3\sigma$ on the EJ309 detector energy resolution, (or ± 120 keVee for the slightly better resolution Stilbene detector) prior to unfolding. Once unfolded, the shifts in the neutron energy peaks (e.g., fusion neutron peak at 2.4 MeV) were determined for both the plus and minus unfolded spectrum.

[0284] This perturbation analysis resulted in a slightly asymmetric neutron energy uncertainty band, biased toward the lower energy, as shown in the figures. The fluence uncertainty (vertical bands) were determined using the GRAVEL unfolding methodology using $\pm 3\sigma$. Note that for clarity, the uncertainty bars were plotted on the figures for only select data points.

[0285] IV. DISCUSSION

[0286] 1. FUSION NEUTRONS

[0287] As shown in FIGS. 11A-C, there are several distinct peaks corresponding to primary fusion neutrons as well as neutrons potentially resulting from subsequent fusion reactions. Kinematic derivations for neutron heating of the deuteron discussed in the

theoretical section above were used to calculate the range of neutron energies caused by the heated fuel. See Table V below.

TABLE V: CALCULATED NEUTRON ENERGIES RESULTING FROM
KINETIC HEATING OF DEUTERIUM FUEL

Generation	Reaction	Cross Section	Projectile Neutron Energy, n (MeV)	Product Deuteron Energy Range, d*, for n-Recoil Angle: 0 to 180° (MeV)	Total Energy ($Q + KE_{d^*}$) (MeV)	Product Neutron Energy Range, n*, for (n*, $^3\text{He}^*$) Recoil Angle: 0 to 180° (MeV)
Initial: Photo neutron heating creating d*	(n,d*)	3	0.145 (average photo neutron energy; 2.9 MeV beam)	0.064 (average d*; 2.9 MeV beam)	0.145	N/A
Gen 1: Fusion reaction with heated d* as projectile	$D(d^*,n^*)^3\text{He}$ $D(d^*,p^*)^3\text{H}$	0.017	N/A	0.064	3.33	2.2 to 2.76
Fusion neutron heating of d*	(n,d*)	2.3	2.2 to 2.76	0.98 to 1.27	4.25 to 4.54	N/A
Gen 2: Subsequent fusion reaction with d* as projectile	$D(d^*,n^*)^3\text{He}$	0.1	N/A	0.98 to 1.27	4.25 to 4.54	1.77 to 4.12 (for d*=0.98 MeV) 1.72 to 4.45 (for d*=1.27 MeV)

[0288] Bremsstrahlung at 2.9 MeV gives rise to photoneutrons with an average neutron energy of 0.145 MeV. Neutron-deuteron recoil then causes a hot deuteron with average energy of 0.064 MeV. Given enhanced screening as described above, a hot deuteron may fuse with a cold deuteron. The separation angle of the (n, 3He) recoil products from 0° to 180° leaves the neutron with 2.2 to 2.76 MeV. This energy spread, coupled with the full-width at half maximum (FWHM) of the instrument, explains some of the broadening of the neutron peaks. A second generation fusion neutron heats a deuteron (n, d*), giving rise to neutron energies from 1.72 to 4.45 MeV. These energies bracket the span of the secondary peak and shoulder of 4 to 4.2 MeV, noted in FIGS. 11A and 11B.

[0289] 2. OTHER ENHANCED NUCLEAR REACTIONS

[0290] FIGS. 11A-C and 12 show evidence of distinct peaks of neutrons having ~4 and ~5 MeV energies. The 4 MeV peak appears sharp, potentially indicating unique nuclear reactions and not simple energy boosting from hot fuel reactions ((n, d*) or (d*, D)). In the highly deuterated metal lattice, which provides shell screening coupled with the plasma filaments from the gamma radiation, it appears that other processes (for example, screened deuteron capture or a modification of an Oppenheimer-Phillips reaction) occurred where a fast neutron is ejected and the proton fuses with the metal nuclei. The theoretical section above calculated very large enhancement factors, on the order of 10^{13} above bare cross sections given ^{166}Er shell and photon-induced Debye screening. Consequently, 50 to 60 keV deuterons may react with the lattice atoms.

[0291] Table VI below presents candidate reactions with the candidate host metal isotopes.

TABLE VI: POSSIBLE REACTIONS WITH BASE METAL RESULTING IN
FAST-NEUTRON EMISSIONS

Reaction	Base Metal Natural Abundance (%)	Q- Value (MeV)	Projectile	Projectile Energy (MeV)	Average Neutron Kinetic Energy (MeV)	Notes: (Decay: Half Life)
$^{166}\text{Er}(^2\text{H},n)^{167}\text{Tm}$	^{166}Er /33.61	2.68	^2H	1.27	3.91	^{167}Tm : Unstable (electron capture: 9.25 d)
$^{167}\text{Er}(^2\text{H},n)^{168}\text{Tm}$	^{167}Er /22.93	3.09	^2H	1.27	4.32	^{168}Tm : Unstable (positron decay: 93 d)
$^{168}\text{Er}(^2\text{H},n)^{169}\text{Tm}$	^{168}Er /26.78	3.35	^2H	1.27	4.58	^{169}Tm : Stable
$^{170}\text{Er}(^2\text{H},n)^{171}\text{Tm}$	^{170}Er /14.93	4.17	^2H	0.87	5.00	^{171}Tm : Unstable (beta decay: 1.92 yr)
$^{170}\text{Er}(^2\text{H},n)^{171}\text{Tm}$	^{170}Er /14.93	4.17	^2H	1.27	5.39	^{171}Tm : Unstable (beta decay: 1.92 yr)
$^{166}\text{Er}(^3\text{He},n)^{168}\text{Yb}$	^{166}Er /33.61	3.50	^3He	0.4	4.00	^{168}Yb : Stable
$^{168}\text{Er}(^3\text{He},n)^{170}\text{Yb}$	^{168}Er /26.78	4.63	^3He	0.4	5.00	^{170}Yb : Stable
$^{170}\text{Er}(^3\text{He},n)^{172}\text{Yb}$	^{170}Er /14.93	6.01	^3He	0.82	6.77	^{172}Yb : Stable
$^{47}\text{Ti}(^2\text{H},n)^{48}\text{V}$	^{47}Ti /7.44	4.61	^2H	0.40	4.91	^{48}V : Unstable (positron decay: 15.9 d)

[0292] Table VI also provides the resulting neutron energies for various “projectile” particles, with product energies consistent with either $\text{D}(d^*, p^*)^3\text{H}^*$ or $\text{D}(d^*, n^*)^3\text{He}^*$. One can see that several reactions may result in 4-MeV neutrons (e.g., $^{166}\text{Er}(^2\text{H}, n)^{167}\text{Tm}$ or $^{166}\text{Er}(^3\text{He}, n)^{168}\text{Yb}$) or 5-MeV neutrons (e.g., $^{170}\text{Er}(^2\text{H}, n)^{171}\text{Tm}$ or $^{168}\text{Er}(^3\text{He}, n)^{170}\text{Yb}$) and for titanium $^{47}\text{Ti}(^2\text{H}, n)^{48}\text{V}$. Note that plausible reactions with titanium explaining the 4 MeV neutrons were not found. Table VI further indicates if the product is stable and the decay/half-life, if unstable.

[0293] The stable isotopes would not be seen during the posttest HPGE gamma scans, nor would the longer half-life isotopes. Post-exposure HPGE gamma analyses did not

reveal isotopes other than ones obtained via neutron capture. Based on the above observations, it appears that both primary D-D fusion and screened deuteron capture on the host isotopes occurred. Evidence of these energetic neutrons indicates attractive nuclear processes are occurring with energetic products (n^* , p^* , t^* , ${}^3\text{He}^*$), which can result in subsequent nuclear processes.

[0294] EXPERIMENTAL CONCLUSIONS

[0295] Per the above, efficient electron screening on localized fusion rates in a dense fuel environment can lead to a significant increase in reaction rates. Based on the theoretical analysis above, neutrons can be exploited to effectively heat deuterons in primary and subsequent reactions, with the well-screened cold target fuel providing screening by shell, conduction, and Compton electrons, resulting in D-D reactions measured by characteristic fusion energy neutrons. This fusion cycle is performed at a high fuel density inside a metal lattice to enable subsequent reactions with the host metal nuclei and other secondary processes.

[0296] More specifically, exposure of deuterated materials, including ErD_3 and TiD_2 , to Bremsstrahlung photon energies (< 2.9 MeV) resulted in both photodissociation-energy neutrons and neutrons with energies consistent with $\text{D(d, n)}{}^3\text{He}$ fusion reactions. Several key ingredients required for fusion reactions are also identified above. Deuterated metals present a unique environment with a high fuel density (10^{22} to 10^{23} D-atoms/cm³), which further increases the fusion reaction probability through shell and lattice electron screening, reducing the D-D fusion barrier.

[0297] Exposing deuterated fuels to a high photon flux creates local plasma conditions near the cold D-fuel, causing additional Debye plasma screening. This

additional screening further increases the Coulomb barrier transparency and further enhances fusion reaction rates. Deuterons were initially heated by photoneutrons with an average energy of 145 keV for the 2.9 MeV beam energy to initiate fusion. However, other neutron sources would also provide the necessary deuteron kinetic energy. Calculations in the theoretical section indicate that neither electrons nor photons alone impart sufficient deuteron kinetic energy to initiate measurable D-D reactions.

[0298] Neutron spectroscopy revealed that both D-D 2.45-MeV fusion neutrons and other processes occurred. The data also indicates that the significant screening enabled charged reaction products (hot d^* , $3He^*$) to interact with the host metal. These interactions may produce the ~ 4 and ~ 5 MeV neutrons, where the screened deuteron capture may have ejected the neutron. Some embodiments thus demonstrate the ability to create enhanced nuclear reactions in highly deuterated metals with the deuteron fuel in a stationary center-of-mass frame. This process eliminates the need to accelerate the deuteron fuel into the target with implications for various practical applications.

[0299] MEDICAL ISOTOPES

[0300] Medical isotopes are a critical aspect of many modern medical diagnostic techniques and procedures. Techniques for radioisotope production include various neutron activation and creation mechanisms to produce an isotope of a specific decay chain, as well as techniques for separation of the desired isotope from the source materials and any ancillary products also produced as part of the activation/creation processes. Activation of a source is typically accomplished by neutron activation in a nuclear reactor, and also by using energetic photons, electrons, protons, alpha particles, and others from a variety of machines specifically designed to accelerate these particles.

Targets in many configurations, both fluids and solids, are impacted, and as a consequence of these impacts, a fraction of the original target material is transmuted, whether isotopic or elemental. Chemical post-processing of targets after activation results in the isolation of the desired radioisotope.

[0301] Isotope-specific systems, and often more than one system for most isotopes, have been designed and redesigned as the machinery used in the production processes has improved. As medical research is an ever-changing field, the number of isotopes of interest varies, and in some cases, the development of a new isotope production technique influences the usage of that isotope in medical procedures. Various radioisotopes may be used to treat cancer and other medical conditions, provide diagnostic information about the functioning of various organs, and sterilize medical equipment, among other applications. Tables VII and VIII below provide lists of isotopes, half-lives, and uses for conventionally produced reactor and cyclotron radioisotopes, respectively.

TABLE VII: REACTOR-PRODUCED RADIOISOTOPES

ISOTOPE:	HALF-LIFE:	APPLICATIONS:
^{213}Bi	46 min	Used for targeted alpha therapy (TAT), especially cancers, due to its high energy (8.4 MeV)
^{137}Cs	30 years	Used for low-intensity sterilization of blood
^{51}Cr	28 days	Used to label red blood cells and to quantify gastrointestinal protein loss
^{60}Co	5.27 years	Formerly used for external beam radiotherapy, now almost universally used for sterilization
^{165}Dy	2 hours	Used as an aggregated hydroxide for synovectomy treatment of arthritis
^{169}Er	9.4 days	Used for relieving arthritis pain in synovial joints
^{166}Ho	26 hours	Being developed for diagnosis and treatment of liver tumors
^{125}I	60 days	Used in cancer brachytherapy (prostate and brain), used diagnostically to evaluate the filtration rate of kidneys and to diagnose deep vein thrombosis in

		the leg, and widely used in radioimmuno-assays to show the presence of hormones in tiny quantities
^{131}I	8 days	Widely used in treating thyroid cancer and in imaging the thyroid, as well as in diagnosis of abnormal liver function, renal (kidney) blood flow, and urinary tract obstruction; while a strong gamma emitter, this isotope is used for beta therapy
^{192}Ir	74 days	Supplied in wire form for use as an internal radiotherapy source for cancer treatment (used then removed); beta emitter
^{59}Fe	46 days	Used in studies of iron metabolism in the spleen
^{212}Pb	10.6 hours	Used in TAT for cancers or alpha radioimmunotherapy, with decay products ^{212}Bi and ^{212}Po delivering the alpha particles; used especially for melanoma, breast cancer, and ovarian cancer
^{177}Lu	6.7 days	Increasingly important as it emits just enough gamma radiation for imaging while the beta radiation does the therapy on small (e.g., endocrine) tumors; half-life is long enough to allow sophisticated preparation for use; usually produced by neutron activation of natural or enriched ^{176}Lu targets
$^{99}\text{Mo}^*$	66 hours	Used as the “parent” in a generator to produce $^{99\text{m}}\text{Tc}$
^{103}Pd	17 days	Used to make brachytherapy permanent implant seeds for early stage prostate cancer
^{32}P	14 days	Used in the treatment of polycythemia vera (excess red blood cells); beta emitter
^{42}K	12 hours	Used for the determination of exchangeable potassium in coronary blood flow
^{186}Re	3.8 days	Used for pain relief in bone cancer; beta emitter with weak gamma for imaging
^{188}Re	17 hours	Used to beta irradiate coronary arteries from an angioplasty balloon
^{153}Sm	47 hours	Highly effective in relieving the pain of secondary cancers lodged in the bone, sold as Quadramet™, and also very effective for prostate and breast cancer; beta emitter.
^{75}Se	120 days	Used in the form of seleno-methionine to study the production of digestive enzymes
^{24}Na	15 hours	Used for studies of electrolytes within the body
^{89}Sr	50 days	Highly effective in reducing the pain of prostate and bone cancer; beta emitter
$^{99\text{m}}\text{Tc}^*$	6 hours	Used to image the skeleton and heart muscle in particular, but also for brain, thyroid, lungs

		(perfusion and ventilation), liver, spleen, kidney (structure and filtration rate), gall bladder, bone marrow, salivary and lacrimal glands, heart blood pool, infection, and numerous specialized medical studies; also produced from ^{99}Mo in a generator
^{133}Xe	5 days	Used for pulmonary (lung) ventilation studies
^{169}Yb	32 days	Used for cerebrospinal fluid studies in the brain
^{177}Yb	1.9 hours	Progenitor of ^{177}Lu
^{90}Y	64 hours	Used for cancer brachytherapy and as a silicate colloid for the relieving the pain of arthritis in larger synovial joints; pure beta emitter and of growing significance in therapy, especially for liver cancer

TABLE VIII: CYCLOTRON-PRODUCED RADIOISOTOPES

ISOTOPE:	HALF-LIFE:	APPLICATIONS:
^{11}C , ^{13}N , ^{15}O , ^{18}F	Not provided	Positron emitters used in PET for studying brain physiology and pathology, and in particular, for localizing epileptic focus, and in dementia, for psychiatry and neuropharmacology studies; also have a significant role in cardiology; ^{18}F in fluorodeoxyglucose (FDG) has become very important in the detection of cancers and the monitoring of progress in their treatment using PET
^{57}Co	272 days	Used as a marker to estimate organ size and for in-vitro diagnostic kits
^{64}Cu	13 hours	Used to study genetic diseases affecting copper metabolism, such as Wilson's and Menke's diseases, and for PET imaging of tumors and therapy
^{67}Cu	2.6 days	Beta emitter, used in therapy
^{18}F	Not provided	Also used as a tracer in the form of fluorothymidine (FLT), fluoromisonidazole (F-miso), and 18F-choline
^{67}Ga	78 hours	Used for tumor imaging and localization of inflammatory lesions (infections)
^{68}Ga	68 min	Positron emitter used in PET and PET-CT units; derived from ^{68}Ge in a generator
^{68}Ge	271 days	Used as the "parent" in a generator to produce ^{68}Ga
^{111}In	2.8 days	Used for specialized diagnostic studies, e.g., brain studies, infection, and colon transit studies
^{123}I	13 hours	Increasingly used for diagnosis of thyroid function; a gamma emitter without the beta radiation of ^{131}I
^{124}I	Not provided	Tracer
$^{81\text{m}}\text{Kr}$	13 sec	Produced from ^{82}Rb (4.6 hours), $^{81\text{m}}\text{Kr}$ gas can yield functional images of pulmonary ventilation, e.g. in

		asthmatic patients, and for the early diagnosis of lung diseases and function
^{82}Rb	1.26 min	Convenient PET agent in myocardial perfusion imaging
^{82}Sr	25 days	Used as the “parent” in a generator to produce ^{82}Rb
^{201}Tl	73 hours	Used for diagnosis of coronary artery disease other heart conditions such as heart muscle death and for location of low-grade lymphomas

[0302] Radioisotopes of cesium, gold, and ruthenium are also used in brachytherapy.

[0303] The (*) designates the importance of ^{99}Mo and $^{99\text{m}}\text{Tc}$ (metastable). ^{99}Mo , and its product $^{99\text{m}}\text{Tc}$, are arguably the most important conventional radioisotopes since $^{99\text{m}}\text{Tc}$ is used in over 80% of diagnostic nuclear medical imaging. ^{99}Mo is by far the most used isotope and has been the focus of many competitive production techniques within the last decade.

[0304] Newer isotope research is adding different and more complex production techniques for ^{99}Mo . Similar situations exist for the roughly 40 isotopes currently in use at medical facilities around the world. Linear accelerator (LINAC) production is also being developed as a new technique.

[0305] However, of the hundreds, if not thousands, of isotopes that are known to exist or are theoretically possible, only dozens are conventionally available for use in modern medicine. This limits treatments to the specific characteristics of these isotopes. Also, many of these isotopes are in limited supply and/or are difficult to obtain. Furthermore, certain medical isotopes must be produced and rapidly delivered to a medical facility in order to be effective. For instance, ^{99}Mo , which is generally a byproduct of the fission of ^{235}U in nuclear reactors, has a half-life of 66 hours. Thus, it is imperative that ^{99}Mo be rapidly separated and processed since half of the supply thereof is lost every 66 hours. Additionally, once $^{99\text{m}}\text{Tc}$ is generated from the ^{99}Mo , half the supply thereof is lost every

six hours. Thus, significant infrastructure, logistical resources and coordination, and expense are required to deliver ^{99m}Tc in time to be useful for imaging applications. Many other radioisotopes have even shorter half-lives, and may decay so rapidly as to be impractical for medical purposes.

[0306] However, per the above, a linear accelerator (LINAC) may be used to facilitate deeply screened fusion. Many hospitals have LINACs, which are rarely in use at night. As such, while a hospital could purchase another LINAC for dedicated use, many would already have the machine without further investment.

[0307] The target medical isotope may be created within a lattice, which may by itself be the material to be transmuted. Other chemical means could subsequently be used to purify the medical isotope. For instance, “moly cows” may be used to purify ^{99m}Tc .

[0308] By using the hospital’s LINAC to create medical isotopes on-site, various benefits may be realized. For instance, the value of the LINAC is increased since its useful operating time is increased. Also, medical isotopes with relatively short half-lives, such as ^{99}Mo and ^{99m}Tc , which have half-lives of 66 hours and 6 hours, respectively. This reduces the production and transportation costs, as well as the risks of exposure of various personnel to radiation during the transportation process. Additionally, it may no longer be necessary to perform chemical separation to obtain the radioisotope of interest. Furthermore, certain radioactive isotopes, such as alpha emitters with half-lives on the order of minutes that may be used to treat cancer, may be created and utilized. Conventionally, this is extremely impracticable or impossible.

[0309] FIG. 13 is a flowchart 1300 illustrating deeply screened fusion reaction process, according to an embodiment of the present invention. The process begins with forming a metal lattice capable of forming a solid matrix with embedded nuclear fuel (such as deuterium or tritium) nuclei at 1310. The deuterated or tritiated metal lattice is then bombarded with high energy neutrons at 1320. The high energy neutrons may be provided by a LINAC, a radioactive element, or both. The high energy neutrons elastically scatter with the nuclear fuel nuclei, heating the fuel nuclei. Some of the nuclear tunnel screened hot and cold fuel nuclei fuse. Hot neutrons are also generated by the nuclear fusion and these elastically scatter with cold fuel nuclei as well, heating the nuclei. Nuclear tunnel screened fuel nuclei fuse, or alternatively, go through an Oppenheimer-Phillips reaction, reacting the screened hot fuel nuclei with a metal lattice nuclei. Additional materials may optionally be included to reflect neutrons escaping the reacting volumes, such as beryllium, materials for participating in nuclear reactions such as lithium deuteride, and/or others.

[0310] In some embodiments, such as for medical isotope production, the products of the reaction itself may be the end result of the process. However, in some embodiments, heat generated by the reactions is used to do work, as in step 1330. For instance, the heat may be used to drive a generator and create electricity and/or to warm a system. The reaction rate may be controlled in some embodiments by adjusting the amount of x-rays and/or gamma rays that are produced by an x-ray device and/or a LINAC at 1340.

[0311] FIG. 14 is an architectural diagram illustrating a fusion reaction system 1400, according to an embodiment of the present invention. System 1400 includes an x-ray

device 1410 and a LINAC 1420 for producing photo neutrons and providing an ionization source. However, in many embodiments, only one of these devices would be included.

[0312] X-ray device 1410 and LINAC 1420 bombard a deeply screened deuterated and/or tritated fuel target 1430 with x-rays and gamma rays, respectively. Fuel 1440 is located on a tantalum braking target 1440. Subjecting deeply screened deuterated and/or tritated fuel target 1430 to x-rays and gamma rays causes fusion reactions to occur, producing heat. This heat is used by a generator 1450 to create electricity (e.g., by heating water, creating steam, and using the steam to turn the generator). A computing system 1460 (e.g., computing system 1500 of FIG. 15) controls operation of x-ray device 1410 and LINAC 1420.

[0313] FIG. 15 is a block diagram illustrating a computing system 1500 configured to control a nuclear reaction rate, according to an embodiment of the present invention. Computing system 1500 includes a bus 1505 or other communication mechanism for communicating information, and processor(s) 1510 coupled to bus 1505 for processing information. Processor(s) 1510 may be any type of general or specific purpose processor, including a central processing unit (CPU) or application specific integrated circuit (ASIC). Processor(s) 1510 may also have multiple processing cores, and at least some of the cores may be configured to perform specific functions. Multi-parallel processing may be used in some embodiments. Computing system 1500 further includes a memory 1515 for storing information and instructions to be executed by processor(s) 1510. Memory 1515 can be comprised of any combination of random access memory (RAM), read only memory (ROM), flash memory, cache, static storage

such as a magnetic or optical disk, or any other types of non-transitory computer-readable media or combinations thereof. Additionally, computing system 1500 includes a communication device 1520, such as a transceiver and antenna, to wirelessly provide access to a communications network.

[0314] Non-transitory computer-readable media may be any available media that can be accessed by processor(s) 1510 and may include volatile media and/or non-volatile media. The media may be removable and/or non-removable media.

[0315] Processor(s) 1510 are further coupled via bus 1505 to a display 1525, such as a Liquid Crystal Display (LCD), for displaying information to a user. A keyboard 1530 and a cursor control device 1535, such as a computer mouse, are further coupled to bus 1505 to enable a user to interface with computing system. However, in certain embodiments such as those for mobile computing implementations, a physical keyboard and mouse may not be present, and the user may interact with the device solely through display 1525 and/or a touchpad (not shown). Any type and combination of input devices may be used as a matter of design choice.

[0316] Memory 1515 stores software modules that provide functionality when executed by processor(s) 1510. The modules include an operating system 1540 for computing system 1500. The modules further include a nuclear reaction control module 1545 that is configured to control the rate of nuclear reactions. Computing system 1500 may include one or more additional functional modules 1550 that include additional functionality.

[0317] One skilled in the art will appreciate that a “system” could be embodied as an embedded computing system, a personal computer, a server, a console, a personal digital

assistant (PDA), a cell phone, a tablet computing device, or any other suitable computing device, or combination of devices. Presenting the above-described functions as being performed by a “system” is not intended to limit the scope of the present invention in any way, but is intended to provide one example of many embodiments of the present invention. Indeed, methods, systems and apparatuses disclosed herein may be implemented in localized and distributed forms consistent with computing technology, including cloud computing systems.

[0318] It should be noted that some of the system features described in this specification have been presented as modules, in order to more particularly emphasize their implementation independence. For example, a module may be implemented as a hardware circuit comprising custom very large scale integration (VLSI) circuits or gate arrays, off-the-shelf semiconductors such as logic chips, transistors, or other discrete components. A module may also be implemented in programmable hardware devices such as field programmable gate arrays, programmable array logic, programmable logic devices, graphics processing units, or the like.

[0319] A module may also be at least partially implemented in software for execution by various types of processors. An identified unit of executable code may, for instance, comprise one or more physical or logical blocks of computer instructions that may, for instance, be organized as an object, procedure, or function. Nevertheless, the executables of an identified module need not be physically located together, but may comprise disparate instructions stored in different locations which, when joined logically together, comprise the module and achieve the stated purpose for the module. Further, modules may be stored on a computer-readable medium, which may be, for

instance, a hard disk drive, flash device, RAM, tape, or any other such medium used to store data.

[0320] Indeed, a module of executable code could be a single instruction, or many instructions, and may even be distributed over several different code segments, among different programs, and across several memory devices. Similarly, operational data may be identified and illustrated herein within modules, and may be embodied in any suitable form and organized within any suitable type of data structure. The operational data may be collected as a single data set, or may be distributed over different locations including over different storage devices, and may exist, at least partially, merely as electronic signals on a system or network.

[0321] It will be readily understood that the components of various embodiments of the present invention, as generally described and illustrated in the figures herein, may be arranged and designed in a wide variety of different configurations. Thus, the detailed description of the embodiments of the present invention, as represented in the attached figures, is not intended to limit the scope of the invention, but is merely representative of selected embodiments of the invention.

[0322] The features, structures, or characteristics of the invention described throughout this specification may be combined in any suitable manner in one or more embodiments. For example, reference throughout this specification to “certain embodiments,” “some embodiments,” or similar language means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, appearances of the phrases “in certain embodiments,” “in some embodiment,” “in other embodiments,” or

similar language throughout this specification do not necessarily all refer to the same group of embodiments and the described features, structures, or characteristics may be combined in any suitable manner in one or more embodiments.

[0323] It should be noted that reference throughout this specification to features, advantages, or similar language does not imply that all of the features and advantages that may be realized with the present invention should be or are in any single embodiment of the invention. Rather, language referring to the features and advantages is understood to mean that a specific feature, advantage, or characteristic described in connection with an embodiment is included in at least one embodiment of the present invention. Thus, discussion of the features and advantages, and similar language, throughout this specification may, but do not necessarily, refer to the same embodiment.

[0324] Furthermore, the described features, advantages, and characteristics of the invention may be combined in any suitable manner in one or more embodiments. One skilled in the relevant art will recognize that the invention can be practiced without one or more of the specific features or advantages of a particular embodiment. In other instances, additional features and advantages may be recognized in certain embodiments that may not be present in all embodiments of the invention.

[0325] One having ordinary skill in the art will readily understand that the invention as discussed above may be practiced with steps in a different order, and/or with hardware elements in configurations which are different than those which are disclosed. Therefore, although the invention has been described based upon these preferred embodiments, it would be apparent to those of skill in the art that certain modifications,

variations, and alternative constructions would be apparent, while remaining within the spirit and scope of the invention.

[0326] In an embodiment, a method includes providing a deeply screened fuel source to enhance nuclear tunneling and to increase a probability of Coulomb scattering at angles of at least 90° . The method also includes subjecting the deeply screened fuel source to energetic neutrons that are in a keV and/or MeV range. In some embodiments, the energetic neutrons are provided by photodisintegration of the fuel via energetic photons provided by a LINAC, directly from a radioactive element, or both. Process control and initiation may be provided by controlling the LINAC to provide certain desired photon flux at desired energy levels, or by inserting the radioactive element to provide hot neutrons into or near the fuel. In the case of a LINAC, the photon flux also generates Compton electrons due to external irradiation by gamma photons, which provide additional screening. In certain embodiments, neutrons are provided throughout the process to deliver sufficient kinetic energy to the reacting nuclei via elastic scattering.

[0327] In some embodiments, the deeply screened fuel source is a deuterated or tritiated metal. In certain embodiments, the deuterated and/or tritiated metal includes lithium, boron, beryllium, and/or one or more high Z metals. In some embodiments, a lattice of the deuterated metal includes an element to be transmuted into a medical isotope. In certain embodiments, the metal lattice includes molybdenum, and the medical isotope includes technetium-99m. The metal lattice may be formed from elements capable of Oppenheimer-Phillips reactions with deuterons even at low energies of hot fuel projectiles (in some embodiments, with deuterons having kinetic

energy in the keV range). In certain embodiments, LiD may be used as the deuterated and/or tritated metal, and/or may be introduced as an additive to participate in reactions following lithium disintegration, resulting in hot deuterons or tritons.

[0328] In certain embodiments, the method further includes controlling a nuclear reaction rate by adjusting a flux of x-rays and/or gamma rays that are produced by an x-ray device and/or a LINAC. In some embodiments, one billion hot neutrons per second or more are produced. In certain embodiments, the method further comprises using heat generated by the nuclear reactions to drive an electric generator.

[0329] In another embodiment, a system includes a LINAC, an x-ray device, or both. The system also includes a deeply screened deuterated and/or tritated fuel source. The LINAC, the x-ray device, or both, are configured to subject the deeply screened deuterated and/or tritated fuel source to x-rays and/or gamma rays, respectively, causing fusion reactions to occur in the deeply screened deuterated and/or tritated fuel source.

[0330] In yet another embodiment, a method includes producing photo neutrons by photodisintegration of a deeply screened deuterated or tritated fuel source a LINAC, the LINAC additionally serving as an ionization source for creation of a deeply screened environment for efficient tunneling and scattering events.

[0331] In still another embodiment, an apparatus includes a deuterated and/or tritated fuel source. The apparatus also includes at least one radioactive material located within the deuterated and/or tritated fuel source, or sufficiently close thereto to provide a predetermined amount of energetic neutrons. In some embodiments, the apparatus further includes a neutron reflector (e.g., beryllium) and/or a participating material (e.g.,

natural uranium, thorium, etc.) to reflect hot neutrons and facilitate further nuclear reactions.

[0332] In another embodiment, an apparatus includes an envelope surrounding a deuterated metal. The envelope may include neutron reflecting elements, gamma reflecting elements, and/or elements capable of participating in subsequent nuclear reactions (e.g., fission by neutrons).

[0333] In yet another embodiment, a method includes providing at least one radioactive material within a deuterated and/or tritated fuel source.

[0334] In still another embodiment, a method is configured to produce hot neutrons with an energy of at least 3 MeV and to provide a natural isotope of lithium, ${}^7\text{Li}$, the hot neutrons reacting with the ${}^7\text{Li}$, resulting in direct production of a neutron cluster, the neutron cluster then being capable of efficiently participating in further nuclear reactions with fuel and lattice elements.

CLAIMS

1. The inventions substantially as shown and/or described herein.

ABSTRACT

Methods and apparatuses for facilitating localized nuclear fusion reactions in deuterated metals enhanced by electron screening are disclosed. Screening is effective not only to enhance nuclear tunneling, but also to increase the probability of Coulomb scattering at large angles, which is a requisite for efficient subsequent tunneling. A deuterated or tritated metal (e.g., lithium deuteride (LiD)) may be used to create an environment where electrons are well screened (i.e., deep screening). The metal lattice provides both the electrons for deep screening and a molecular “cage” so the deuterons themselves can be at a high density. An external source of x-rays or gamma rays may be utilized to enhance further deep screening within the metal lattice. The metal lattice is bombarded with neutrons from a neutron source that provides a desired rate of neutron production. The deeply screened fusion and other nuclear reaction processes are mediated by elastic collisions with hot neutrons, some provided by external means, and some generated by the nuclear reactions. Process multiplication events of the hot neutrons used to efficiently transfer kinetic energy for local heating of the nuclear fuel can be designed using materials such as LiD or other materials capable of participating in Oppenheimer-Phillips, even at low energy.